

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	pn98247	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	06 Hour 35 Min 12 Sec
Total Counter :	1701032	Total Running Time :	769 Hour 35 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.60	kN	No		
HEP :	25.0 %	17.89	kN	Yes	10	Rotations
HCP :	2.0 %	14.60	kN	Yes	15	Times
Ref :		14.31	kN			
LCP :	2.0 %	14.02	kN	Yes	15	Times
LEP :	25.0 %	10.73	kN	Yes	10	Rotations
LSP :	30.0 %	10.02	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.05	kN	Min :	0.98	kN	Punch NO.;	67
SD :	2.80	%	Max :	1.14	kN	Punch NO.;	35
Mean Main Pressure :	14.46	kN	Min :	12.98	kN	Punch NO.;	50
SD :	4.40	%	Max :	16.46	kN	Punch NO.;	35
Filling Depth :	Increase ;	424	Times	Decrease ;	455	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	6.00	mm	Current Cam :	Cam B	
Main Air pressure :	0.742	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	8
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	74
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	1701032	Tablets			
A.W.C Counter :	1692965	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	35 (0.0%)	Tablets
GOOD :	1692922 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	pn98247	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	06 Hour 35 Min 12 Sec
Total Counter :	1701032	Total Running Time :	769 Hour 35 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.04	kN	No		
HEP :	25.0 %	16.38	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.37	kN	Yes 15	Times	
Ref :		13.11	kN			
LCP :	2.0 %	12.84	kN	Yes 15	Times	
LEP :	25.0 %	9.83	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.17	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.15	kN	Min :	1.11	kN	Punch NO.;	19
		1.80	%	Max :	1.22	kN	Punch NO.;	1
Mean Main Pressure :		13.05	kN	Min :	12.03	kN	Punch NO.;	50
	SD :	3.10	%	Max :	14.05	kN	Punch NO.;	44
Filling Depth :	Increase ;	141	Times	Decrease ;	131	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.54	mm	Main Thickness ;	1.55	mm
Filling Depth :	5.90	mm	Current Cam :	Cam B	
Main Air pressure :	0.742	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	4
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	74
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	1701032	Tablets			
A.W.C Counter :	1692965	Tablets			
HEP :	8 (0.0%)	Tablets	LEP :	35 (0.0%)	Tablets
GOOD :	1692922 (100.0%)	Tablets			