

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SETRA50MG STSH4A00    |
| User ID :        | ka98463       | Batch NO. :          | SHM2500450            |
| Print Interval : | 50000 Tablets | Running Time :       | 08 Hour 31 Min 12 Sec |
| Total Counter :  | 2201382       | Total Running Time : | 771 Hour 31 Min       |
| Station :        | Station 1     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 18       | %       | Manual ;           | 12           | RPM       |
| Filling Cam :                      |             | Cam B    |         | Cam Range :        | Min :        | 2.50 mm   |
|                                    |             | 4.5-10mm |         |                    | Max :        | 8.00 mm   |
| Target Quantity :                  |             | 6000000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 200      | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 180      | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |             | 5.0      | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 4.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 1.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 18.70    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 17.98    | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 14.67    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 14.39    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 14.10    | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 10.79    | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 10.07    | kN      | No                 |              |           |
| SD limit :                         | 20.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 20.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 1 Rotations |          |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |                |       |            |       |       |            |    |
|----------------------|----------------|-------|------------|-------|-------|------------|----|
| Mean Pre Pressure :  | 1.07           | kN    | Min :      | 0.99  | kN    | Punch NO.; | 1  |
| SD :                 | 2.80           | %     | Max :      | 1.17  | kN    | Punch NO.; | 35 |
| Mean Main Pressure : | 14.36          | kN    | Min :      | 12.82 | kN    | Punch NO.; | 1  |
| SD :                 | 4.20           | %     | Max :      | 16.31 | kN    | Punch NO.; | 35 |
| Filling Depth :      | Increase ; 558 | Times | Decrease ; | 578   | Times |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 5        | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.60    | mm  | Pre Thickness ;  | 2.61     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.50    | mm  | Main Thickness ; | 1.51     | mm           |
| Filling Depth :               | 6.33    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.726   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 117     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 113     | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 35 |
| Lower Punch :    | Average ; | 0.09 | kN |             |    |
|                  | Max ;     | 0.10 | kN | Max Punch ; | 71 |
| Ejection Force : | Average ; | 0.09 | kN |             |    |
|                  | Max ;     | 0.13 | kN | Max Punch ; | 45 |

### Tablet Data (N/A)

|                 |                     |         |       |           |         |
|-----------------|---------------------|---------|-------|-----------|---------|
| Total Counter : | 2201382             | Tablets |       |           |         |
| A.W.C Counter : | 2192960             | Tablets |       |           |         |
| HEP :           | 10 (0.0%)           | Tablets | LEP : | 35 (0.0%) | Tablets |
| GOOD :          | 2192915<br>(100.0%) | Tablets |       |           |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SETRA50MG STSH4A00    |
| User ID :        | ka98463       | Batch NO. :          | SHM2500450            |
| Print Interval : | 50000 Tablets | Running Time :       | 08 Hour 31 Min 12 Sec |
| Total Counter :  | 2201382       | Total Running Time : | 771 Hour 31 Min       |
| Station :        | Station 2     |                      |                       |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 18        | %       | Manual ;           | 12           | RPM       |
| Filling Cam :                      |        | Cam B     |         | Cam Range :        | Min :        | 2.50 mm   |
|                                    |        | 4.5-10mm  |         |                    | Max :        | 8.00 mm   |
| Target Quantity :                  |        | 6000000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 200       | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 180       | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |        | 5.0       | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 1.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 17.22     | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 16.56     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 13.51     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 13.25     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 12.98     | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 9.93      | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 9.27      | kN      | No                 |              |           |
| SD limit :                         | 20.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 20.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 1      | Rotations |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.15       | kN  | Min : | 1.09       | kN  | Punch NO.; | 21 |
| SD :                 | 1.80       | %   | Max : | 1.19       | kN  | Punch NO.; | 34 |
| Mean Main Pressure : | 13.23      | kN  | Min : | 12.07      | kN  | Punch NO.; | 16 |
| SD :                 | 3.20       | %   | Max : | 14.18      | kN  | Punch NO.; | 77 |
| Filling Depth :      | Increase ; | 165 | Times | Decrease ; | 155 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 5        | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.60    | mm  | Pre Thickness ;  | 2.61     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.54    | mm  | Main Thickness ; | 1.55     | mm           |
| Filling Depth :               | 5.95    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.726   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 117     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 113     | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.06 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 4  |
| Lower Punch :    | Average ; | 0.09 | kN |             |    |
|                  | Max ;     | 0.10 | kN | Max Punch ; | 71 |
| Ejection Force : | Average ; | 0.09 | kN |             |    |
|                  | Max ;     | 0.13 | kN | Max Punch ; | 45 |

### Tablet Data (N/A)

|                 |                     |         |       |           |         |
|-----------------|---------------------|---------|-------|-----------|---------|
| Total Counter : | 2201382             | Tablets |       |           |         |
| A.W.C Counter : | 2192960             | Tablets |       |           |         |
| HEP :           | 10 (0.0%)           | Tablets | LEP : | 35 (0.0%) | Tablets |
| GOOD :          | 2192915<br>(100.0%) | Tablets |       |           |         |