

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPR 400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500240
Print Interval :	50000 Tablets	Running Time :	02 Hour 43 Min 27 Sec
Total Counter :	400184	Total Running Time :	788 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	12	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.64	kN	No		
HEP :	25.0 %	20.80	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	16.98	kN	Yes 15	Times	
Ref :		16.64	kN			
LCP :	2.0 %	16.31	kN	Yes 15	Times	
LEP :	25.0 %	12.48	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	11.65	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.27	kN	Min :	1.21	kN	Punch NO.;	20
SD :	2.00	%	Max :	1.34	kN	Punch NO.;	12
Mean Main Pressure :	17.26	kN	Min :	15.81	kN	Punch NO.;	4
SD :	4.30	%	Max :	19.25	kN	Punch NO.;	22
Filling Depth :	Increase ;	361	Times	Decrease ;	323	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.50	mm
Filling Depth :	8.20	mm	Current Cam :	Cam C	
Main Air pressure :	0.770	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.47	kN		
	Max ;	0.56	kN	Max Punch ;	1
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	38
Ejection Force :	Average ;	0.12	kN		
	Max ;	0.20	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	400184	Tablets			
A.W.C Counter :	388688	Tablets			
HEP :	165 (0.0%)	Tablets	LEP :	397 (0.1%)	Tablets
GOOD :	388126 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPR 400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500240
Print Interval :	50000 Tablets	Running Time :	02 Hour 43 Min 27 Sec
Total Counter :	400184	Total Running Time :	788 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	12	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.04	kN	No		
HEP :	25.0 %	22.16	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	18.08	kN	Yes 15	Times	
Ref :		17.73	kN			
LCP :	2.0 %	17.37	kN	Yes 15	Times	
LEP :	25.0 %	13.30	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	12.41	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.04	kN	Min :	1.00	kN	Punch NO.;	35
SD :	2.50	%	Max :	1.10	kN	Punch NO.;	19
Mean Main Pressure :	17.76	kN	Min :	15.74	kN	Punch NO.;	40
SD :	5.10	%	Max :	19.58	kN	Punch NO.;	18
Filling Depth :	Increase ;	252	Times	Decrease ;	211	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.60	mm
Filling Depth :	8.27	mm	Current Cam :	Cam C	
Main Air pressure :	0.770	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.47	kN		
	Max ;	0.54	kN	Max Punch ;	39
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	38
Ejection Force :	Average ;	0.12	kN		
	Max ;	0.20	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	400184	Tablets			
A.W.C Counter :	388688	Tablets			
HEP :	165 (0.0%)	Tablets	LEP :	397 (0.1%)	Tablets
GOOD :	388126 (99.9%)	Tablets			