

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | IBUPR 400MG<br>STIU2B00 |
| User ID :        | pm98770       | Batch NO. :          | IUM2500240              |
| Print Interval : | 50000 Tablets | Running Time :       | 08 Hour 50 Min 50 Sec   |
| Total Counter :  | 1300568       | Total Running Time : | 794 Hour 48 Min         |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 90       | %       | Manual ;           | 12           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 2025000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 60       | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 40       | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |             | 5.0      | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 4.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 23.29    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 22.40    | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 18.28    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 17.92    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 17.56    | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 13.44    | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 12.54    | kN      | No                 |              |           |
| SD limit :                         | 20.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 20.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 1 Rotations |          |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.53       | kN  | Min : | 1.49       | kN  | Punch NO.; | 30 |
| SD :                 | 3.10       | %   | Max : | 1.77       | kN  | Punch NO.; | 36 |
| Mean Main Pressure : | 17.97      | kN  | Min : | 16.38      | kN  | Punch NO.; | 4  |
| SD :                 | 4.60       | %   | Max : | 19.90      | kN  | Punch NO.; | 24 |
| Filling Depth :      | Increase ; | 797 | Times | Decrease ; | 729 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 18       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.20    | mm  | Pre Thickness ;  | 2.20     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.50    | mm  | Main Thickness ; | 1.50     | mm           |
| Filling Depth :               | 9.01    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.765   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 24      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 4       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.30 | kN |             |    |
|                  | Max ;     | 0.41 | kN | Max Punch ; | 44 |
| Lower Punch :    | Average ; | 0.16 | kN |             |    |
|                  | Max ;     | 0.64 | kN | Max Punch ; | 6  |
| Ejection Force : | Average ; | 0.18 | kN |             |    |
|                  | Max ;     | 0.89 | kN | Max Punch ; | 36 |

### Tablet Data (N/A)

|                 |                    |         |       |            |         |
|-----------------|--------------------|---------|-------|------------|---------|
| Total Counter : | 1300568            | Tablets |       |            |         |
| A.W.C Counter : | 1284647            | Tablets |       |            |         |
| HEP :           | 299 (0.0%)         | Tablets | LEP : | 397 (0.0%) | Tablets |
| GOOD :          | 1283951<br>(99.9%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | IBUPR 400MG<br>STIU2B00 |
| User ID :        | pm98770       | Batch NO. :          | IUM2500240              |
| Print Interval : | 50000 Tablets | Running Time :       | 08 Hour 50 Min 50 Sec   |
| Total Counter :  | 1300568       | Total Running Time : | 794 Hour 48 Min         |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 90        | %       | Manual ;           | 12           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 2025000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.400     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 60        | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 40        | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |        | 5.0       | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 22.61     | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 21.74     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 17.74     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 17.39     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 17.04     | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 13.04     | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 12.17     | kN      | No                 |              |           |
| SD limit :                         | 20.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 20.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 1      | Rotations |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.36       | kN  | Min : | 1.31       | kN  | Punch NO.; | 7  |
| SD :                 | 4.70       | %   | Max : | 1.68       | kN  | Punch NO.; | 36 |
| Mean Main Pressure : | 17.04      | kN  | Min : | 15.80      | kN  | Punch NO.; | 47 |
| SD :                 | 4.30       | %   | Max : | 18.71      | kN  | Punch NO.; | 29 |
| Filling Depth :      | Increase ; | 721 | Times | Decrease ; | 637 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 20      | RPM | Capacity :       | 127200   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 18       | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.20    | mm  | Pre Thickness ;  | 2.20     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.65    | mm  | Main Thickness ; | 1.65     | mm           |
| Filling Depth :               | 9.33    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.765   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 24      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 4       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.31 | kN |             |    |
|                  | Max ;     | 0.39 | kN | Max Punch ; | 44 |
| Lower Punch :    | Average ; | 0.16 | kN |             |    |
|                  | Max ;     | 0.64 | kN | Max Punch ; | 6  |
| Ejection Force : | Average ; | 0.18 | kN |             |    |
|                  | Max ;     | 0.89 | kN | Max Punch ; | 36 |

### Tablet Data (N/A)

|                 |                    |         |       |            |         |
|-----------------|--------------------|---------|-------|------------|---------|
| Total Counter : | 1300568            | Tablets |       |            |         |
| A.W.C Counter : | 1284647            | Tablets |       |            |         |
| HEP :           | 299 (0.0%)         | Tablets | LEP : | 397 (0.0%) | Tablets |
| GOOD :          | 1283951<br>(99.9%) | Tablets |       |            |         |