

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	sj97904	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	02 Hour 19 Min 47 Sec
Total Counter :	600452	Total Running Time :	802 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.46	kN	No		
HEP :	25.0 %	17.75	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.48	kN	Yes 10	Times	
Ref :		14.20	kN			
LCP :	2.0 %	13.91	kN	Yes 10	Times	
LEP :	25.0 %	10.65	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.94	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.56	kN	Min :	2.38	kN	Punch NO.;	19
SD :	2.40	%	Max :	2.67	kN	Punch NO.;	42
Mean Main Pressure :	14.21	kN	Min :	12.91	kN	Punch NO.;	16
SD :	3.30	%	Max :	15.25	kN	Punch NO.;	61
Filling Depth :	Increase ; 36	Times	Decrease ; 52	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.41	mm	Main Thickness ;	1.91	mm
Filling Depth :	7.55	mm	Current Cam :	Cam C	
Main Air pressure :	0.762	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	44	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.50	kN		
	Max ;	0.62	kN	Max Punch ;	66
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.39	kN	Max Punch ;	58
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	600452	Tablets			
A.W.C Counter :	593668	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	593667	Tablets			
	(100.0%)				

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	sj97904	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	02 Hour 19 Min 47 Sec
Total Counter :	600452	Total Running Time :	802 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.14	kN	No		
HEP :	25.0 %	19.37	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.80	kN	Yes 10	Times	
Ref :		15.49	kN			
LCP :	2.0 %	15.18	kN	Yes 10	Times	
LEP :	25.0 %	11.62	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.85	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.62	kN	Min :	2.52	kN	Punch NO.;	9
		1.40	%	Max :	2.72	kN	Punch NO.;	42
Mean Main Pressure :		15.67	kN	Min :	14.95	kN	Punch NO.;	16
	SD :	2.00	%	Max :	16.47	kN	Punch NO.;	52
Filling Depth :	Increase ;	28	Times	Decrease ;	46	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.97	mm
Filling Depth :	7.53	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.762	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	44	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.50	kN		
	Max ;	0.62	kN	Max Punch ;	66
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.39	kN	Max Punch ;	58
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	600452	Tablets			
A.W.C Counter :	593668	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	593667 (100.0%)	Tablets			