

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	rp98927	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	00 Hour 05 Min 07 Sec
Total Counter :	8472	Total Running Time :	811 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.34	kN	No		
HEP :	25.0 %	15.72	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.82	kN	Yes	10 Times	
Ref :		12.57	kN			
LCP :	2.0 %	12.32	kN	Yes	10 Times	
LEP :	25.0 %	9.43	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.80	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.02	kN	Min :	1.98	kN	Punch NO.;	42
SD :	1.10	%	Max :	2.12	kN	Punch NO.;	21
Mean Main Pressure :	12.72	kN	Min :	11.65	kN	Punch NO.;	27
SD :	4.30	%	Max :	14.20	kN	Punch NO.;	34
Filling Depth :	Increase ;	4	Times	Decrease ;	2	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	9.34	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.774	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.23	kN	Max Punch ;	41
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.19	kN	Max Punch ;	19
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.29	kN	Max Punch ;	48

Tablet Data (N/A)

Total Counter :	8472	Tablets			
A.W.C Counter :	4133	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	4133 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	rp98927	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	00 Hour 05 Min 07 Sec
Total Counter :	8472	Total Running Time :	811 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.62	kN	No		
HEP :	25.0 %	18.87	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.39	kN	Yes	10 Times	
Ref :		15.09	kN			
LCP :	2.0 %	14.79	kN	Yes	10 Times	
LEP :	25.0 %	11.32	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.80	kN	Min :	1.76	kN	Punch NO.;	5
		1.10	%	Max :	1.88	kN	Punch NO.;	48
Mean Main Pressure :		15.20	kN	Min :	13.71	kN	Punch NO.;	1
	SD :	4.10	%	Max :	16.97	kN	Punch NO.;	10
Filling Depth :	Increase ;	4	Times	Decrease ;	1	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.50	mm
Filling Depth :	8.90	mm	Current Cam :	Cam C	
Main Air pressure :	0.774	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.25	kN	Max Punch ;	41
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.19	kN	Max Punch ;	19
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.29	kN	Max Punch ;	48

Tablet Data (N/A)

Total Counter :	8472	Tablets			
A.W.C Counter :	4186	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	4186 (100.0%)	Tablets			