

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	rp98927	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	02 Hour 23 Min 58 Sec
Total Counter :	301780	Total Running Time :	814 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.57	kN	No		
HEP :	25.0 %	14.97	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	12.22	kN	Yes	10	Times
Ref :		11.98	kN			
LCP :	2.0 %	11.74	kN	Yes	10	Times
LEP :	25.0 %	8.98	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	8.38	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.06	kN	Min :	2.01	kN	Punch NO.;	28
SD :	0.90	%	Max :	2.12	kN	Punch NO.;	27
Mean Main Pressure :	12.45	kN	Min :	10.18	kN	Punch NO.;	35
SD :	6.00	%	Max :	14.59	kN	Punch NO.;	3
Filling Depth :	Increase ;	124	Times	Decrease ;	118	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	9.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.766	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.27	kN	Max Punch ;	43
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.22	kN	Max Punch ;	27
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.30	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	301780	Tablets			
A.W.C Counter :	297300	Tablets			
HEP :	24 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	297275 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	rp98927	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	02 Hour 23 Min 58 Sec
Total Counter :	301780	Total Running Time :	814 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.06	kN	No		
HEP :	25.0 %	19.29	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.74	kN	Yes	10 Times	
Ref :		15.43	kN			
LCP :	2.0 %	15.13	kN	Yes	10 Times	
LEP :	25.0 %	11.58	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.80	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.85	kN	Min :	1.80	kN	Punch NO.;	45
SD :	1.20	%	Max :	1.93	kN	Punch NO.;	23
Mean Main Pressure :	15.64	kN	Min :	13.90	kN	Punch NO.;	49
SD :	4.60	%	Max :	17.03	kN	Punch NO.;	24
Filling Depth :	Increase ;	60	Times	Decrease ;	50	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.55	mm
Filling Depth :	9.29	mm	Current Cam :	Cam C	
Main Air pressure :	0.766	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.27	kN	Max Punch ;	43
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.20	kN	Max Punch ;	27
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.29	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	301780	Tablets			
A.W.C Counter :	297300	Tablets			
HEP :	24 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	297275 (100.0%)	Tablets			