

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	rp98927	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	04 Hour 18 Min 55 Sec
Total Counter :	544770	Total Running Time :	816 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.66	kN	No		
HEP :	25.0 %	14.09	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	11.50	kN	Yes 10	Times	
Ref :		11.27	kN			
LCP :	2.0 %	11.05	kN	Yes 10	Times	
LEP :	25.0 %	8.46	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.89	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.07	kN	Min :	2.03	kN	Punch NO.;	28
SD :	1.10	%	Max :	2.15	kN	Punch NO.;	19
Mean Main Pressure :	11.24	kN	Min :	9.36	kN	Punch NO.;	42
SD :	5.90	%	Max :	12.43	kN	Punch NO.;	30
Filling Depth :	Increase ; 122	Times	Decrease ;	109	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.59	mm	Main Thickness ;	1.60	mm
Filling Depth :	9.68	mm	Current Cam :	Cam C	
Main Air pressure :	0.779	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.23	kN	Max Punch ;	43
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.27	kN	Max Punch ;	19
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.40	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	544770	Tablets			
A.W.C Counter :	540005	Tablets			
HEP :	60 (0.0%)	Tablets	LEP :	13 (0.0%)	Tablets
GOOD :	539932 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	rp98927	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	04 Hour 18 Min 55 Sec
Total Counter :	544770	Total Running Time :	816 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.90	kN	No		
HEP :	25.0 %	18.17	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	14.83	kN	Yes	10 Times	
Ref :		14.54	kN			
LCP :	2.0 %	14.25	kN	Yes	10 Times	
LEP :	25.0 %	10.90	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.18	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.94	kN	Min :	1.90	kN	Punch NO.;	20
SD :	1.30	%	Max :	2.04	kN	Punch NO.;	19
Mean Main Pressure :	14.51	kN	Min :	12.40	kN	Punch NO.;	49
SD :	4.60	%	Max :	15.77	kN	Punch NO.;	30
Filling Depth :	Increase ;	23	Times	Decrease ;	24	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.59	mm	Main Thickness ;	1.60	mm
Filling Depth :	9.29	mm	Current Cam :	Cam C	
Main Air pressure :	0.779	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.23	kN	Max Punch ;	43
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.27	kN	Max Punch ;	19
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.40	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	544770	Tablets			
A.W.C Counter :	540005	Tablets			
HEP :	60 (0.0%)	Tablets	LEP :	13 (0.0%)	Tablets
GOOD :	539932 (100.0%)	Tablets			