

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	sj97904	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	14 Hour 33 Min 53 Sec
Total Counter :	1845214	Total Running Time :	826 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	25	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.05	kN	No		
HEP :	25.0 %	17.35	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.16	kN	Yes 10	Times	
Ref :		13.88	kN			
LCP :	2.0 %	13.61	kN	Yes 10	Times	
LEP :	25.0 %	10.41	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.21	kN	Min :	2.15	kN	Punch NO.;	32
SD :	2.10	%	Max :	2.36	kN	Punch NO.;	8
Mean Main Pressure :	15.02	kN	Min :	13.41	kN	Punch NO.;	26
SD :	7.00	%	Max :	17.54	kN	Punch NO.;	8
Filling Depth :	Increase ;	548	Times	Decrease ;	540	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	9.18	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.778	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.30	kN	Max Punch ;	40
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.41	kN	Max Punch ;	6
Ejection Force :	Average ;	0.13	kN		
	Max ;	0.76	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1845214	Tablets			
A.W.C Counter :	1839420	Tablets			
HEP :	621 (0.0%)	Tablets	LEP :	248 (0.0%)	Tablets
GOOD :	1838551 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	sj97904	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	14 Hour 33 Min 53 Sec
Total Counter :	1845214	Total Running Time :	826 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	110	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.29	kN	No		
HEP :	25.0 %	16.63	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.57	kN	Yes 10	Times	
Ref :		13.30	kN			
LCP :	2.0 %	13.03	kN	Yes 10	Times	
LEP :	25.0 %	9.98	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.38	kN	Min :	2.31	kN	Punch NO.;	35
SD :	2.00	%	Max :	2.54	kN	Punch NO.;	6
Mean Main Pressure :	14.30	kN	Min :	9.38	kN	Punch NO.;	51
SD :	16.80	%	Max :	16.86	kN	Punch NO.;	28
Filling Depth :	Increase ;	449	Times	Decrease ;	450	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.69	mm	Main Thickness ;	1.70	mm
Filling Depth :	9.23	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.778	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.30	kN	Max Punch ;	40
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.31	kN	Max Punch ;	6
Ejection Force :	Average ;	0.13	kN		
	Max ;	0.67	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1845214	Tablets			
A.W.C Counter :	1839420	Tablets			
HEP :	621 (0.0%)	Tablets	LEP :	248 (0.0%)	Tablets
GOOD :	1838551 (100.0%)	Tablets			