

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pb97604	Batch NO. :	MVM2500513
Print Interval :	50000 Tablets	Running Time :	14 Hour 43 Min 45 Sec
Total Counter :	1867492	Total Running Time :	841 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	81	%	Manual ;	34	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.82	kN	No		
HEP :	25.0 %	17.14	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.98	kN	Yes 10	Times	
Ref :		13.71	kN			
LCP :	2.0 %	13.44	kN	Yes 10	Times	
LEP :	25.0 %	10.28	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.60	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.23	kN	Min :	2.18	kN	Punch NO.;	28
SD :	1.50	%	Max :	2.41	kN	Punch NO.;	8
Mean Main Pressure :	13.56	kN	Min :	12.70	kN	Punch NO.;	19
SD :	3.50	%	Max :	14.49	kN	Punch NO.;	3
Filling Depth :	Increase ;	327	Times	Decrease ;	299	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	9.26	mm	Current Cam :	Cam C	
Main Air pressure :	0.778	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	42
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.49	kN	Max Punch ;	8
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.57	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1867492	Tablets			
A.W.C Counter :	1857738	Tablets			
HEP :	927 (0.0%)	Tablets	LEP :	229 (0.0%)	Tablets
GOOD :	1856582 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pb97604	Batch NO. :	MVM2500513
Print Interval :	50000 Tablets	Running Time :	14 Hour 43 Min 45 Sec
Total Counter :	1867492	Total Running Time :	841 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	81	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.89	kN	No		
HEP :	25.0 %	16.24	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.25	kN	Yes 10	Times	
Ref :		12.99	kN			
LCP :	2.0 %	12.74	kN	Yes 10	Times	
LEP :	25.0 %	9.75	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.10	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.13	kN	Min :	2.10	kN	Punch NO.;	16
SD :	1.60	%	Max :	2.33	kN	Punch NO.;	8
Mean Main Pressure :	13.45	kN	Min :	12.22	kN	Punch NO.;	27
SD :	7.50	%	Max :	19.36	kN	Punch NO.;	23
Filling Depth :	Increase ;	380	Times	Decrease ;	371	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	9.14	mm	Current Cam :	Cam C	
Main Air pressure :	0.778	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.22	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.49	kN	Max Punch ;	8
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.57	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1867492	Tablets			
A.W.C Counter :	1857738	Tablets			
HEP :	927 (0.0%)	Tablets	LEP :	229 (0.0%)	Tablets
GOOD :	1856582 (99.9%)	Tablets			