

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500613
Print Interval :	50000 Tablets	Running Time :	05 Hour 30 Min 59 Sec
Total Counter :	700238	Total Running Time :	848 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	34	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.48	kN	No		
HEP :	25.0 %	15.84	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.93	kN	Yes 10	Times	
Ref :		12.67	kN			
LCP :	2.0 %	12.42	kN	Yes 10	Times	
LEP :	25.0 %	9.51	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.87	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.10	kN	Min :	2.07	kN	Punch NO.;	4
SD :	1.30	%	Max :	2.25	kN	Punch NO.;	8
Mean Main Pressure :	12.61	kN	Min :	11.25	kN	Punch NO.;	27
SD :	3.90	%	Max :	13.87	kN	Punch NO.;	41
Filling Depth :	Increase ;	35	Times	Decrease ;	39	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	8.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	41
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.33	kN	Max Punch ;	8
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.38	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	700238	Tablets			
A.W.C Counter :	698382	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	698376 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500613
Print Interval :	50000 Tablets	Running Time :	05 Hour 30 Min 59 Sec
Total Counter :	700238	Total Running Time :	848 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.08	kN	No		
HEP :	25.0 %	15.46	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.61	kN	Yes 10	Times	
Ref :		12.37	kN			
LCP :	2.0 %	12.12	kN	Yes 10	Times	
LEP :	25.0 %	9.27	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.97	kN	Min :	1.90	kN	Punch NO.;	8
SD :	0.90	%	Max :	2.02	kN	Punch NO.;	44
Mean Main Pressure :	12.26	kN	Min :	11.19	kN	Punch NO.;	53
SD :	5.70	%	Max :	14.03	kN	Punch NO.;	20
Filling Depth :	Increase ;	15	Times	Decrease ;	19	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	8.84	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	41
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.35	kN	Max Punch ;	8
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.39	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	700238	Tablets			
A.W.C Counter :	698382	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	698376 (100.0%)	Tablets			