

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	am98755	Batch NO. :	MVM2500613
Print Interval :	50000 Tablets	Running Time :	09 Hour 51 Min 26 Sec
Total Counter :	1250436	Total Running Time :	852 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.92	kN	No		
HEP :	25.0 %	15.30	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.49	kN	Yes 10	Times	
Ref :		12.24	kN			
LCP :	2.0 %	12.00	kN	Yes 10	Times	
LEP :	25.0 %	9.18	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.18	kN	Min :	2.15	kN	Punch NO.;	15
SD :	0.70	%	Max :	2.22	kN	Punch NO.;	21
Mean Main Pressure :	12.15	kN	Min :	10.74	kN	Punch NO.;	27
SD :	3.90	%	Max :	13.13	kN	Punch NO.;	35
Filling Depth :	Increase ; 168	Times	Decrease ;	151	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	9.07	mm	Current Cam :	Cam C	
Main Air pressure :	0.814	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	19
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	31
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.19	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1250436	Tablets			
A.W.C Counter :	1245160	Tablets			
HEP :	71 (0.0%)	Tablets	LEP :	160 (0.0%)	Tablets
GOOD :	1244929 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	am98755	Batch NO. :	MVM2500613
Print Interval :	50000 Tablets	Running Time :	09 Hour 51 Min 26 Sec
Total Counter :	1250436	Total Running Time :	852 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	51	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.61	kN	No		
HEP :	25.0 %	15.01	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.25	kN	Yes	10 Times	
Ref :		12.01	kN			
LCP :	2.0 %	11.77	kN	Yes	10 Times	
LEP :	25.0 %	9.01	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.41	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.11	kN	Min :	2.08	kN	Punch NO.;	5
SD :	0.60	%	Max :	2.14	kN	Punch NO.;	8
Mean Main Pressure :	12.06	kN	Min :	10.65	kN	Punch NO.;	27
SD :	5.50	%	Max :	13.63	kN	Punch NO.;	35
Filling Depth :	Increase ;	65	Times	Decrease ;	81	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	8.95	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.814	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	19
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	31
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.19	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1250436	Tablets			
A.W.C Counter :	1245160	Tablets			
HEP :	71 (0.0%)	Tablets	LEP :	160 (0.0%)	Tablets
GOOD :	1244929 (100.0%)	Tablets			