

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	rp98927	Batch NO. :	MVM2500713
Print Interval :	50000 Tablets	Running Time :	02 Hour 08 Min 49 Sec
Total Counter :	300098	Total Running Time :	860 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.52	kN	No		
HEP :	25.0 %	14.92	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	12.18	kN	Yes	10	Times
Ref :		11.94	kN			
LCP :	2.0 %	11.70	kN	Yes	10	Times
LEP :	25.0 %	8.95	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	8.36	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.16	kN	Min :	2.12	kN	Punch NO.;	28
SD :	0.80	%	Max :	2.20	kN	Punch NO.;	8
Mean Main Pressure :	11.78	kN	Min :	10.67	kN	Punch NO.;	40
SD :	4.00	%	Max :	13.18	kN	Punch NO.;	50
Filling Depth :	Increase ;	478	Times	Decrease ;	443	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	8.96	mm	Current Cam :	Cam C	
Main Air pressure :	0.802	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.30	kN	Max Punch ;	17
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	44
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	300098	Tablets			
A.W.C Counter :	298728	Tablets			
HEP :	48 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	298680 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	rp98927	Batch NO. :	MVM2500713
Print Interval :	50000 Tablets	Running Time :	02 Hour 08 Min 49 Sec
Total Counter :	300098	Total Running Time :	860 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.37	kN	No		
HEP :	25.0 %	14.78	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.06	kN	Yes 10	Times	
Ref :		11.82	kN			
LCP :	2.0 %	11.59	kN	Yes 10	Times	
LEP :	25.0 %	8.87	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.28	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.05	kN	Min :	1.99	kN	Punch NO.;	15
SD :	1.00	%	Max :	2.09	kN	Punch NO.;	6
Mean Main Pressure :	12.05	kN	Min :	10.77	kN	Punch NO.;	53
SD :	5.40	%	Max :	13.32	kN	Punch NO.;	2
Filling Depth :	Increase ;	194	Times	Decrease ;	211	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	8.94	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.802	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.30	kN	Max Punch ;	17
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	46
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	300098	Tablets			
A.W.C Counter :	298728	Tablets			
HEP :	48 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	298680 (100.0%)	Tablets			