

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pb97604	Batch NO. :	MVM2500713
Print Interval :	50000 Tablets	Running Time :	12 Hour 09 Min 30 Sec
Total Counter :	1700732	Total Running Time :	870 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.31	kN	No		
HEP :	25.0 %	15.69	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.80	kN	Yes	10 Times	
Ref :		12.55	kN			
LCP :	2.0 %	12.30	kN	Yes	10 Times	
LEP :	25.0 %	9.41	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.78	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.22	kN	Min :	2.18	kN	Punch NO.;	16
SD :	0.90	%	Max :	2.27	kN	Punch NO.;	9
Mean Main Pressure :	12.32	kN	Min :	11.45	kN	Punch NO.;	38
SD :	3.30	%	Max :	13.27	kN	Punch NO.;	18
Filling Depth :	Increase ;	709	Times	Decrease ;	684	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	9.02	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.34	kN	Max Punch ;	28
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	19
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1700732	Tablets			
A.W.C Counter :	1697635	Tablets			
HEP :	252 (0.0%)	Tablets	LEP :	237 (0.0%)	Tablets
GOOD :	1697146 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pb97604	Batch NO. :	MVM2500713
Print Interval :	50000 Tablets	Running Time :	12 Hour 09 Min 30 Sec
Total Counter :	1700732	Total Running Time :	870 Hour 17 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.13	kN	No		
HEP :	25.0 %	15.51	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.66	kN	Yes	10 Times	
Ref :		12.41	kN			
LCP :	2.0 %	12.16	kN	Yes	10 Times	
LEP :	25.0 %	9.31	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.39	kN	Min :	2.33	kN	Punch NO.;	2
SD :	0.70	%	Max :	2.43	kN	Punch NO.;	22
Mean Main Pressure :	12.52	kN	Min :	11.09	kN	Punch NO.;	51
SD :	5.40	%	Max :	14.04	kN	Punch NO.;	8
Filling Depth :	Increase ;	645	Times	Decrease ;	661	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	9.12	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.33	kN	Max Punch ;	28
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	19
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1700732	Tablets			
A.W.C Counter :	1697635	Tablets			
HEP :	252 (0.0%)	Tablets	LEP :	237 (0.0%)	Tablets
GOOD :	1697146 (100.0%)	Tablets			