

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	sj97904	Batch NO. :	MVM2500713
Print Interval :	50000 Tablets	Running Time :	14 Hour 03 Min 42 Sec
Total Counter :	1967136	Total Running Time :	872 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.31	kN	No		
HEP :	25.0 %	15.69	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.80	kN	Yes	10 Times	
Ref :		12.55	kN			
LCP :	2.0 %	12.30	kN	Yes	10 Times	
LEP :	25.0 %	9.41	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.78	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.22	kN	Min :	2.16	kN	Punch NO.;	28
SD :	0.80	%	Max :	2.27	kN	Punch NO.;	1
Mean Main Pressure :	10.24	kN	Min :	8.44	kN	Punch NO.;	42
SD :	5.10	%	Max :	11.16	kN	Punch NO.;	17
Filling Depth :	Increase ;	771	Times	Decrease ;	704	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	9.43	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.775	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.30	kN	Max Punch ;	30
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	46
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1967136	Tablets			
A.W.C Counter :	1963647	Tablets			
HEP :	283 (0.0%)	Tablets	LEP :	281 (0.0%)	Tablets
GOOD :	1963083 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	sj97904	Batch NO. :	MVM2500713
Print Interval :	50000 Tablets	Running Time :	14 Hour 03 Min 42 Sec
Total Counter :	1967136	Total Running Time :	872 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.13	kN	No		
HEP :	25.0 %	15.51	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.66	kN	Yes 10	Times	
Ref :		12.41	kN			
LCP :	2.0 %	12.16	kN	Yes 10	Times	
LEP :	25.0 %	9.31	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.42	kN	Min :	2.39	kN	Punch NO.;	7
SD :	0.70	%	Max :	2.46	kN	Punch NO.;	24
Mean Main Pressure :	12.44	kN	Min :	11.19	kN	Punch NO.;	51
SD :	4.90	%	Max :	13.65	kN	Punch NO.;	28
Filling Depth :	Increase ;	762	Times	Decrease ;	775	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	9.21	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.775	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.30	kN	Max Punch ;	30
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	46
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1967136	Tablets			
A.W.C Counter :	1963647	Tablets			
HEP :	283 (0.0%)	Tablets	LEP :	281 (0.0%)	Tablets
GOOD :	1963083 (100.0%)	Tablets			