

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Prop 40mg STPJ2B00
User ID :	pr190041	Batch NO. :	PJM2500240
Print Interval :	50000 Tablets	Running Time :	01 Hour 35 Min 28 Sec
Total Counter :	250178	Total Running Time :	887 Hour 59 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	35	%	Manual ;	11	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	30.18	kN	No		
HEP :	25.0 %	29.02	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	23.68	kN	Yes 10	Times	
Ref :		23.22	kN			
LCP :	2.0 %	22.75	kN	Yes 10	Times	
LEP :	25.0 %	17.41	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	16.25	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.83	kN	Min :	1.80	kN	Punch NO.;	15
SD :	1.30	%	Max :	1.90	kN	Punch NO.;	23
Mean Main Pressure :	23.15	kN	Min :	21.91	kN	Punch NO.;	53
SD :	2.50	%	Max :	24.37	kN	Punch NO.;	45
Filling Depth :	Increase ; 3	Times	Decrease ;	23	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	5.59	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.795	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.35	kN		
	Max ;	0.41	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	4
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	250178	Tablets			
A.W.C Counter :	246111	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	246111 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Prop 40mg STPJ2B00
User ID :	pr190041	Batch NO. :	PJM2500240
Print Interval :	50000 Tablets	Running Time :	01 Hour 35 Min 28 Sec
Total Counter :	250178	Total Running Time :	887 Hour 59 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	35	%	Manual ;	11	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.09	kN	No		
HEP :	25.0 %	27.98	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	22.83	kN	Yes	10	Times
Ref :		22.38	kN			
LCP :	2.0 %	21.93	kN	Yes	10	Times
LEP :	25.0 %	16.79	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	15.67	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.75	kN	Min :	1.72	kN	Punch NO.;	29
		0.90	%	Max :	1.80	kN	Punch NO.;	5
Mean Main Pressure :		22.26	kN	Min :	19.93	kN	Punch NO.;	1
	SD :	4.10	%	Max :	24.70	kN	Punch NO.;	17
Filling Depth :	Increase ;	3	Times	Decrease ;	6	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	5.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.795	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.35	kN		
	Max ;	0.41	kN	Max Punch ;	51
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	4
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	250178	Tablets			
A.W.C Counter :	246164	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	246164 (100.0%)	Tablets			