

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Prop 40mg STPJ2B00
User ID :	pb97604	Batch NO. :	PJM2500440
Print Interval :	50000 Tablets	Running Time :	02 Hour 12 Min 07 Sec
Total Counter :	350136	Total Running Time :	913 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	11	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.27	kN	No		
HEP :	25.0 %	28.14	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	22.97	kN	Yes 10	Times	
Ref :		22.52	kN			
LCP :	2.0 %	22.06	kN	Yes 10	Times	
LEP :	25.0 %	16.89	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	15.76	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.89	kN	Min :	1.83	kN	Punch NO.;	44
SD :	1.60	%	Max :	1.96	kN	Punch NO.;	39
Mean Main Pressure :	22.61	kN	Min :	21.50	kN	Punch NO.;	53
SD :	2.60	%	Max :	23.75	kN	Punch NO.;	45
Filling Depth :	Increase ; 46	Times	Decrease ; 75	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.57	mm	Main Thickness ;	1.58	mm
Filling Depth :	6.03	mm	Current Cam :	Cam B	
Main Air pressure :	0.744	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.37	kN		
	Max ;	0.43	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	22
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	350136	Tablets			
A.W.C Counter :	347750	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	347750 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Prop 40mg STPJ2B00
User ID :	pb97604	Batch NO. :	PJM2500440
Print Interval :	50000 Tablets	Running Time :	02 Hour 12 Min 07 Sec
Total Counter :	350136	Total Running Time :	913 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	39	%	Manual ;	11	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.25	kN	No		
HEP :	25.0 %	28.13	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	22.95	kN	Yes 10	Times	
Ref :		22.50	kN			
LCP :	2.0 %	22.05	kN	Yes 10	Times	
LEP :	25.0 %	16.88	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	15.75	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.80	kN	Min :	1.77	kN	Punch NO.;	11
SD :	1.00	%	Max :	1.87	kN	Punch NO.;	53
Mean Main Pressure :	22.60	kN	Min :	20.72	kN	Punch NO.;	53
SD :	3.80	%	Max :	24.77	kN	Punch NO.;	9
Filling Depth :	Increase ; 16	Times	Decrease ; 32	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	5.62	mm	Current Cam :	Cam B	
Main Air pressure :	0.744	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.36	kN		
	Max ;	0.42	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	22
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	350136	Tablets			
A.W.C Counter :	347750	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	347750 (100.0%)	Tablets			