

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Prop 40mg STPJ2B00
User ID :	yu98249	Batch NO. :	PJM2500640
Print Interval :	50000 Tablets	Running Time :	11 Hour 32 Min 11 Sec
Total Counter :	1835996	Total Running Time :	947 Hour 25 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	11	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	30.75	kN	No		
HEP :	25.0 %	29.57	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	24.13	kN	Yes 10	Times	
Ref :		23.66	kN			
LCP :	2.0 %	23.18	kN	Yes 10	Times	
LEP :	25.0 %	17.74	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	16.56	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.86	kN	Min :	1.81	kN	Punch NO.;	19
SD :	1.30	%	Max :	1.91	kN	Punch NO.;	13
Mean Main Pressure :	23.40	kN	Min :	22.25	kN	Punch NO.;	26
SD :	2.90	%	Max :	24.95	kN	Punch NO.;	17
Filling Depth :	Increase ; 0	Times	Decrease ;	19	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.56	mm	Main Thickness ;	1.57	mm
Filling Depth :	5.66	mm	Current Cam :	Cam B	
Main Air pressure :	0.803	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.36	kN		
	Max ;	0.42	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	41
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.10	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	1835996	Tablets			
A.W.C Counter :	1831838	Tablets			
HEP :	0 (0%)	Tablets	LEP :	5 (0.0%)	Tablets
GOOD :	1831833 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Prop 40mg STPJ2B00
User ID :	yu98249	Batch NO. :	PJM2500640
Print Interval :	50000 Tablets	Running Time :	11 Hour 32 Min 11 Sec
Total Counter :	1835996	Total Running Time :	947 Hour 25 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	39	%	Manual ;	11	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.53	kN	No		
HEP :	25.0 %	30.32	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	24.74	kN	Yes	10	Times
Ref :		24.26	kN			
LCP :	2.0 %	23.77	kN	Yes	10	Times
LEP :	25.0 %	18.19	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	16.98	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.04	kN	Min :	2.00	kN	Punch NO.;	34
		1.10	%	Max :	2.10	kN	Punch NO.;	38
Mean Main Pressure :		24.33	kN	Min :	21.88	kN	Punch NO.;	38
	SD :	4.20	%	Max :	26.78	kN	Punch NO.;	9
Filling Depth :	Increase ;	5	Times	Decrease ;	8	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	5.76	mm	Current Cam :	Cam B	
Main Air pressure :	0.803	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.36	kN		
	Max ;	0.41	kN	Max Punch ;	40
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	41
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.10	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	1835996	Tablets			
A.W.C Counter :	1831891	Tablets			
HEP :	0 (0%)	Tablets	LEP :	5 (0.0%)	Tablets
GOOD :	1831886 (100.0%)	Tablets			