

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	pb97604	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	00 Hour 07 Min 18 Sec
Total Counter :	13008	Total Running Time :	948 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.19	kN	No		
HEP :	25.0 %	17.49	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.27	kN	Yes 10	Times	
Ref :		13.99	kN			
LCP :	2.0 %	13.71	kN	Yes 10	Times	
LEP :	25.0 %	10.50	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.80	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.06	kN	Min :	4.55	kN	Punch NO.;	32
		4.60	%	Max :	5.57	kN	Punch NO.;	7
Mean Main Pressure :		13.83	kN	Min :	12.34	kN	Punch NO.;	14
	SD :	3.60	%	Max :	14.90	kN	Punch NO.;	42
Filling Depth :	Increase ;	0	Times	Decrease ;	2	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.60	mm	Pre Thickness ;	0.80	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.11	mm	Main Thickness ;	0.62	mm
Filling Depth :	3.84	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.642	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.18	kN	Max Punch ;	39
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	13
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	13008	Tablets			
A.W.C Counter :	1904	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1904 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	pb97604	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	00 Hour 07 Min 19 Sec
Total Counter :	13038	Total Running Time :	948 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	11	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.62	kN	No		
HEP :	25.0 %	18.87	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.40	kN	Yes 10	Times	
Ref :		15.10	kN			
LCP :	2.0 %	14.79	kN	Yes 10	Times	
LEP :	25.0 %	11.32	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.56	kN	Min :	4.03	kN	Punch NO.;	32
SD :	4.80	%	Max :	5.04	kN	Punch NO.;	53
Mean Main Pressure :	15.04	kN	Min :	13.45	kN	Punch NO.;	22
SD :	3.80	%	Max :	16.15	kN	Punch NO.;	33
Filling Depth :	Increase ; 1	Times	Decrease ; 0	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	3.79	mm	Pre Thickness ;	0.80	mm
Main Upper Punch Position ;	3.48	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	0.62	mm
Filling Depth :	3.83	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.642	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.18	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	13
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	13038	Tablets			
A.W.C Counter :	1904	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1904 (100.0%)	Tablets			