

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	pb97604	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	00 Hour 26 Min 19 Sec
Total Counter :	50010	Total Running Time :	948 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.19	kN	No		
HEP :	25.0 %	17.49	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.27	kN	Yes 10	Times	
Ref :		13.99	kN			
LCP :	2.0 %	13.71	kN	Yes 10	Times	
LEP :	25.0 %	10.50	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.80	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.12	kN	Min :	4.69	kN	Punch NO.;	38
		4.80	%	Max :	5.84	kN	Punch NO.;	9
Mean Main Pressure :		13.90	kN	Min :	12.89	kN	Punch NO.;	18
	SD :	3.30	%	Max :	14.99	kN	Punch NO.;	48
Filling Depth :	Increase ;	22	Times	Decrease ;	18	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	117000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.60	mm	Pre Thickness ;	0.80	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.11	mm	Main Thickness ;	0.62	mm
Filling Depth :	4.02	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.827	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.18	kN	Max Punch ;	11
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	19
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	50010	Tablets			
A.W.C Counter :	38822	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	11 (0.0%)	Tablets
GOOD :	38810 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	pb97604	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	00 Hour 26 Min 19 Sec
Total Counter :	50010	Total Running Time :	948 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	11	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.59	kN	No		
HEP :	25.0 %	18.84	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.37	kN	Yes 10	Times	
Ref :		15.07	kN			
LCP :	2.0 %	14.77	kN	Yes 10	Times	
LEP :	25.0 %	11.30	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.55	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.63	kN	Min :	4.12	kN	Punch NO.;	38
SD :	6.10	%	Max :	5.23	kN	Punch NO.;	53
Mean Main Pressure :	15.13	kN	Min :	13.28	kN	Punch NO.;	22
SD :	5.10	%	Max :	16.59	kN	Punch NO.;	41
Filling Depth :	Increase ; 16	Times	Decrease ; 8	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	117000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	3.79	mm	Pre Thickness ;	0.80	mm
Main Upper Punch Position ;	3.48	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	0.62	mm
Filling Depth :	3.92	mm	Current Cam :	Cam B	
Main Air pressure :	0.827	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.18	kN	Max Punch ;	11
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	19
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	50010	Tablets			
A.W.C Counter :	38822	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	11 (0.0%)	Tablets
GOOD :	38810	Tablets			
	(100.0%)				