

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	01 Hour 07 Min 15 Sec
Total Counter :	150068	Total Running Time :	949 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.33	kN	No		
HEP :	25.0 %	17.63	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	14.38	kN	Yes	10	Times
Ref :		14.10	kN			
LCP :	2.0 %	13.82	kN	Yes	10	Times
LEP :	25.0 %	10.58	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	9.87	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.74	kN	Min :	5.17	kN	Punch NO.;	45
SD :	5.00	%	Max :	6.42	kN	Punch NO.;	9
Mean Main Pressure :	14.67	kN	Min :	13.42	kN	Punch NO.;	27
SD :	3.60	%	Max :	16.09	kN	Punch NO.;	58
Filling Depth :	Increase ;	102	Times	Decrease ;	73	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.55	mm	Pre Thickness ;	0.75	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.11	mm	Main Thickness ;	0.62	mm
Filling Depth :	4.80	mm	Current Cam :	Cam B	
Main Air pressure :	0.809	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.12	kN	Max Punch ;	17
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	42
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	150068	Tablets			
A.W.C Counter :	135773	Tablets			
HEP :	16 (0.0%)	Tablets	LEP :	12 (0.0%)	Tablets
GOOD :	135745 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	01 Hour 07 Min 15 Sec
Total Counter :	150068	Total Running Time :	949 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.40	kN	No		
HEP :	25.0 %	17.69	kN	Yes	10	Rotations
HCP :	2.0 %	14.44	kN	Yes	10	Times
Ref :		14.15	kN			
LCP :	2.0 %	13.87	kN	Yes	10	Times
LEP :	25.0 %	10.61	kN	Yes	10	Rotations
LSP :	30.0 %	9.91	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.85	kN	Min :	4.31	kN	Punch NO.;	38
SD :	5.80	%	Max :	5.57	kN	Punch NO.;	52
Mean Main Pressure :	13.83	kN	Min :	11.97	kN	Punch NO.;	22
SD :	5.40	%	Max :	15.79	kN	Punch NO.;	41
Filling Depth :	Increase ;	59	Times	Decrease ;	50	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	3.70	mm	Pre Thickness ;	0.71	mm
Main Upper Punch Position ;	3.48	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	0.62	mm
Filling Depth :	4.44	mm	Current Cam :	Cam B	
Main Air pressure :	0.809	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.12	kN	Max Punch ;	17
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	42
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	150068	Tablets			
A.W.C Counter :	135773	Tablets			
HEP :	16 (0.0%)	Tablets	LEP :	12 (0.0%)	Tablets
GOOD :	135745 (100.0%)	Tablets			