

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	02 Hour 00 Min 11 Sec
Total Counter :	276874	Total Running Time :	950 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.24	kN	No		
HEP :	25.0 %	17.54	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.31	kN	Yes 10	Times	
Ref :		14.03	kN			
LCP :	2.0 %	13.75	kN	Yes 10	Times	
LEP :	25.0 %	10.52	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.82	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.14	kN	Min :	4.47	kN	Punch NO.;	32
		6.00	%	Max :	5.91	kN	Punch NO.;	9
Mean Main Pressure :		12.95	kN	Min :	11.66	kN	Punch NO.;	22
	SD :	4.90	%	Max :	14.73	kN	Punch NO.;	31
Filling Depth :	Increase ;	229	Times	Decrease ;	195	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.55	mm	Pre Thickness ;	0.75	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.11	mm	Main Thickness ;	0.62	mm
Filling Depth :	4.32	mm	Current Cam :	Cam B	
Main Air pressure :	0.815	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	18
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	60
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	276874	Tablets			
A.W.C Counter :	259525	Tablets			
HEP :	136 (0.1%)	Tablets	LEP :	19 (0.0%)	Tablets
GOOD :	259370 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	02 Hour 00 Min 11 Sec
Total Counter :	276874	Total Running Time :	950 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.15	kN	No		
HEP :	25.0 %	18.42	kN	Yes	10	Rotations
HCP :	2.0 %	15.03	kN	Yes	10	Times
Ref :		14.73	kN			
LCP :	2.0 %	14.44	kN	Yes	10	Times
LEP :	25.0 %	11.05	kN	Yes	10	Rotations
LSP :	30.0 %	10.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	5.09	kN	Min :	4.56	kN	Punch NO.;	38
		5.80	%	Max :	5.82	kN	Punch NO.;	57
Mean Main Pressure :		14.80	kN	Min :	12.98	kN	Punch NO.;	22
	SD :	5.20	%	Max :	16.88	kN	Punch NO.;	41
Filling Depth :	Increase ;	116	Times	Decrease ;	119	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	3.70	mm	Pre Thickness ;	0.71	mm
Main Upper Punch Position ;	3.48	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	0.62	mm
Filling Depth :	3.91	mm	Current Cam :	Cam B	
Main Air pressure :	0.815	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	18
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	60
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	276874	Tablets			
A.W.C Counter :	259525	Tablets			
HEP :	136 (0.1%)	Tablets	LEP :	19 (0.0%)	Tablets
GOOD :	259370 (99.9%)	Tablets			