

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	02 Hour 10 Min 08 Sec
Total Counter :	300122	Total Running Time :	950 Hour 41 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.24	kN	No		
HEP :	25.0 %	17.54	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.31	kN	Yes 10	Times	
Ref :		14.03	kN			
LCP :	2.0 %	13.75	kN	Yes 10	Times	
LEP :	25.0 %	10.52	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.82	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.56	kN	Min :	4.93	kN	Punch NO.;	32
SD :	5.40	%	Max :	6.24	kN	Punch NO.;	17
Mean Main Pressure :	14.15	kN	Min :	12.99	kN	Punch NO.;	35
SD :	3.80	%	Max :	15.31	kN	Punch NO.;	48
Filling Depth :	Increase ;	249	Times	Decrease ;	207	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.55	mm	Pre Thickness ;	0.75	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.11	mm	Main Thickness ;	0.62	mm
Filling Depth :	4.80	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	20
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	54
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	300122	Tablets			
A.W.C Counter :	282795	Tablets			
HEP :	136 (0.0%)	Tablets	LEP :	19 (0.0%)	Tablets
GOOD :	282640 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	02 Hour 10 Min 08 Sec
Total Counter :	300122	Total Running Time :	950 Hour 41 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.15	kN	No		
HEP :	25.0 %	18.42	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	15.03	kN	Yes	10	Times
Ref :		14.73	kN			
LCP :	2.0 %	14.44	kN	Yes	10	Times
LEP :	25.0 %	11.05	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	10.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	5.10	kN	Min :	4.44	kN	Punch NO.;	38
SD :	5.90	%	Max :	5.99	kN	Punch NO.;	53
Mean Main Pressure :	14.74	kN	Min :	12.76	kN	Punch NO.;	22
SD :	4.90	%	Max :	16.62	kN	Punch NO.;	42
Filling Depth :	Increase ;	123	Times	Decrease ;	124	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	3.70	mm	Pre Thickness ;	0.71	mm
Main Upper Punch Position ;	3.48	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	0.62	mm
Filling Depth :	3.97	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	20
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	54
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	300122	Tablets			
A.W.C Counter :	282795	Tablets			
HEP :	136 (0.0%)	Tablets	LEP :	19 (0.0%)	Tablets
GOOD :	282640 (99.9%)	Tablets			