

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG,STJU1B00
User ID :	ka98463	Batch NO. :	JUM2500105
Print Interval :	50000 Tablets	Running Time :	00 Hour 49 Min 36 Sec
Total Counter :	85988	Total Running Time :	951 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	49	%	Manual ;	10	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		180000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.04	kN	No		
HEP :	25.0 %	29.85	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	24.35	kN	Yes	10	Times
Ref :		23.88	kN			
LCP :	2.0 %	23.40	kN	Yes	10	Times
LEP :	25.0 %	17.91	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	16.71	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.66	kN	Min :	1.63	kN	Punch NO.;	18
SD :	0.70	%	Max :	1.69	kN	Punch NO.;	1
Mean Main Pressure :	23.31	kN	Min :	20.64	kN	Punch NO.;	27
SD :	4.10	%	Max :	25.08	kN	Punch NO.;	19
Filling Depth :	Increase ;	51	Times	Decrease ;	25	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	1.66	mm
Filling Depth :	9.29	mm	Current Cam :	Cam C	
Main Air pressure :	0.774	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	2
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	8
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	85988	Tablets			
A.W.C Counter :	78530	Tablets			
HEP :	41 (0.1%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	78489 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : ka98463 Print Interval : 50000 Tablets Total Counter : 86022 Station : Station 2	Product Name : BUME 5 MG,STJU1B00 Batch NO. : JUM2500105 Running Time : 00 Hour 49 Min 37 Sec Total Running Time : 951 Hour 39 Min
---	---

Setting Value

Feeder :	Auto ;	49	%	Manual ;	10	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		180000	Tablets			
Oil Lubrication :		0.000	MPa			
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.90	kN	No		
HEP :	25.0 %	27.79	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	22.68	kN	Yes 10	Times	
Ref :		22.23	kN			
LCP :	2.0 %	21.79	kN	Yes 10	Times	
LEP :	25.0 %	16.68	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	15.56	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.71	kN	Min :	1.68	kN	Punch NO.;	47
		0.60	%	Max :	1.73	kN	Punch NO.;	17
Mean Main Pressure :		22.12	kN	Min :	19.54	kN	Punch NO.;	53
	SD :	5.60	%	Max :	24.42	kN	Punch NO.;	49
Filling Depth :	Increase ;	35	Times	Decrease ;	24	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.70	mm	Main Thickness ;	1.70	mm
Filling Depth :	8.66	mm	Current Cam :	Cam C	
Main Air pressure :	0.774	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	40
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	8
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	86022	Tablets			
A.W.C Counter :	78530	Tablets			
HEP :	41 (0.1%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	78489 (99.9%)	Tablets			