

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	rp98927	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	01 Hour 08 Min 18 Sec
Total Counter :	200086	Total Running Time :	953 Hour 39 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	107	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.11	kN	No		
HEP :	25.0 %	13.57	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	11.07	kN	Yes	10 Times	
Ref :		10.85	kN			
LCP :	2.0 %	10.64	kN	Yes	10 Times	
LEP :	25.0 %	8.14	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.60	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.67	kN	Min :	2.63	kN	Punch NO.;	28
SD :	0.50	%	Max :	2.70	kN	Punch NO.;	24
Mean Main Pressure :	10.96	kN	Min :	9.79	kN	Punch NO.;	13
SD :	5.50	%	Max :	12.19	kN	Punch NO.;	35
Filling Depth :	Increase ;	105	Times	Decrease ;	75	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.86	mm	Current Cam :	Cam B	
Main Air pressure :	0.794	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	3
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	200086	Tablets			
A.W.C Counter :	194220	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	20 (0.0%)	Tablets
GOOD :	194183 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	rp98927	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	01 Hour 08 Min 18 Sec
Total Counter :	200086	Total Running Time :	953 Hour 39 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.22	kN	No		
HEP :	25.0 %	14.64	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	11.95	kN	Yes	10 Times	
Ref :		11.71	kN			
LCP :	2.0 %	11.48	kN	Yes	10 Times	
LEP :	25.0 %	8.78	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.20	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.61	kN	Min :	2.55	kN	Punch NO.;	2
SD :	1.20	%	Max :	2.67	kN	Punch NO.;	37
Mean Main Pressure :	11.93	kN	Min :	10.54	kN	Punch NO.;	27
SD :	5.60	%	Max :	13.46	kN	Punch NO.;	28
Filling Depth :	Increase ;	47	Times	Decrease ;	48	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.55	mm	Current Cam :	Cam B	
Main Air pressure :	0.794	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.14	kN	Max Punch ;	42
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	200086	Tablets			
A.W.C Counter :	194220	Tablets			
HEP :	17 (0.0%)	Tablets	LEP :	20 (0.0%)	Tablets
GOOD :	194183 (100.0%)	Tablets			