

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	pb97604	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	05 Hour 04 Min 14 Sec
Total Counter :	900310	Total Running Time :	957 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	107	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.52	kN	No		
HEP :	25.0 %	14.92	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.17	kN	Yes	10 Times	
Ref :		11.94	kN			
LCP :	2.0 %	11.70	kN	Yes	10 Times	
LEP :	25.0 %	8.95	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.35	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.80	kN	Min :	2.75	kN	Punch NO.;	42
SD :	0.60	%	Max :	2.83	kN	Punch NO.;	51
Mean Main Pressure :	11.83	kN	Min :	10.76	kN	Punch NO.;	12
SD :	5.60	%	Max :	13.67	kN	Punch NO.;	41
Filling Depth :	Increase ;	229	Times	Decrease ;	215	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.72	mm	Current Cam :	Cam B	
Main Air pressure :	0.766	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	39
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	900310	Tablets			
A.W.C Counter :	894195	Tablets			
HEP :	200 (0.0%)	Tablets	LEP :	28 (0.0%)	Tablets
GOOD :	893967 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	pb97604	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	05 Hour 04 Min 14 Sec
Total Counter :	900310	Total Running Time :	957 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.76	kN	No		
HEP :	25.0 %	15.15	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.36	kN	Yes	10 Times	
Ref :		12.12	kN			
LCP :	2.0 %	11.88	kN	Yes	10 Times	
LEP :	25.0 %	9.09	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.48	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.68	kN	Min :	2.63	kN	Punch NO.;	43
SD :	0.80	%	Max :	2.72	kN	Punch NO.;	10
Mean Main Pressure :	12.24	kN	Min :	10.89	kN	Punch NO.;	52
SD :	6.40	%	Max :	14.47	kN	Punch NO.;	3
Filling Depth :	Increase ;	205	Times	Decrease ;	204	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.56	mm	Current Cam :	Cam B	
Main Air pressure :	0.766	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	24
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	900310	Tablets			
A.W.C Counter :	894195	Tablets			
HEP :	200 (0.0%)	Tablets	LEP :	28 (0.0%)	Tablets
GOOD :	893967 (100.0%)	Tablets			