

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	pb97604	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	06 Hour 28 Min 38 Sec
Total Counter :	1150430	Total Running Time :	959 Hour 0 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	108	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		180	Min	Supply Time ;	0.8	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.52	kN	No		
HEP :	25.0 %	14.92	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.17	kN	Yes 10	Times	
Ref :		11.94	kN			
LCP :	2.0 %	11.70	kN	Yes 10	Times	
LEP :	25.0 %	8.95	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.35	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.86	kN	Min :	2.82	kN	Punch NO.;	5
SD :	0.60	%	Max :	2.91	kN	Punch NO.;	51
Mean Main Pressure :	11.67	kN	Min :	10.26	kN	Punch NO.;	21
SD :	5.80	%	Max :	13.40	kN	Punch NO.;	46
Filling Depth :	Increase ; 308	Times	Decrease ;	289	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.62	mm	Current Cam :	Cam B	
Main Air pressure :	0.804	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	148	Min			
Lower Punch Remain Time (S2):	129	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.20	kN	Max Punch ;	24
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1150430	Tablets			
A.W.C Counter :	1142920	Tablets			
HEP :	239 (0.0%)	Tablets	LEP :	32 (0.0%)	Tablets
GOOD :	1142649 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	pb97604	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	06 Hour 28 Min 38 Sec
Total Counter :	1150430	Total Running Time :	959 Hour 0 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		180	Min	Supply Time ;	0.8	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.76	kN	No		
HEP :	25.0 %	15.15	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.36	kN	Yes	10 Times	
Ref :		12.12	kN			
LCP :	2.0 %	11.88	kN	Yes	10 Times	
LEP :	25.0 %	9.09	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.48	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.78	kN	Min :	2.74	kN	Punch NO.;	30
SD :	0.60	%	Max :	2.82	kN	Punch NO.;	24
Mean Main Pressure :	12.02	kN	Min :	10.62	kN	Punch NO.;	21
SD :	7.10	%	Max :	14.69	kN	Punch NO.;	46
Filling Depth :	Increase ;	261	Times	Decrease ;	266	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.38	mm	Current Cam :	Cam B	
Main Air pressure :	0.804	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	148	Min			
Lower Punch Remain Time (S2):	129	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	3
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.20	kN	Max Punch ;	24
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1150430	Tablets			
A.W.C Counter :	1142920	Tablets			
HEP :	239 (0.0%)	Tablets	LEP :	32 (0.0%)	Tablets
GOOD :	1142649 (100.0%)	Tablets			