

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	sj97904	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	12 Hour 42 Min 56 Sec
Total Counter :	2262398	Total Running Time :	965 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	109	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	0.8	Sec
Lower Punch Interval Time(S2) ;		45	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.66	kN	No		
HEP :	25.0 %	15.05	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.28	kN	Yes 10	Times	
Ref :		12.04	kN			
LCP :	2.0 %	11.80	kN	Yes 10	Times	
LEP :	25.0 %	9.03	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.43	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.95	kN	Min :	2.91	kN	Punch NO.;	47
SD :	0.60	%	Max :	3.00	kN	Punch NO.;	11
Mean Main Pressure :	12.05	kN	Min :	10.61	kN	Punch NO.;	52
SD :	5.60	%	Max :	13.53	kN	Punch NO.;	16
Filling Depth :	Increase ;	517	Times	Decrease ;	497	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	31	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.44	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	44
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.17	kN	Max Punch ;	6
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	2262398	Tablets			
A.W.C Counter :	2253710	Tablets			
HEP :	357 (0.0%)	Tablets	LEP :	147 (0.0%)	Tablets
GOOD :	2253206 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	sj97904	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	12 Hour 42 Min 56 Sec
Total Counter :	2262398	Total Running Time :	965 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	0.8	Sec
Lower Punch Interval Time(S2) ;		45	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.38	kN	No		
HEP :	25.0 %	15.75	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.85	kN	Yes	10 Times	
Ref :		12.60	kN			
LCP :	2.0 %	12.35	kN	Yes	10 Times	
LEP :	25.0 %	9.45	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.82	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.07	kN	Min :	3.03	kN	Punch NO.;	43
SD :	0.60	%	Max :	3.12	kN	Punch NO.;	18
Mean Main Pressure :	12.88	kN	Min :	11.23	kN	Punch NO.;	52
SD :	6.60	%	Max :	14.60	kN	Punch NO.;	16
Filling Depth :	Increase ;	475	Times	Decrease ;	493	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.43	mm
Filling Depth :	7.47	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	44
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.17	kN	Max Punch ;	6
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	2262398	Tablets			
A.W.C Counter :	2253763	Tablets			
HEP :	357 (0.0%)	Tablets	LEP :	147 (0.0%)	Tablets
GOOD :	2253259 (100.0%)	Tablets			