

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	ms88737	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	20 Hour 30 Min 12 Sec
Total Counter :	3651648	Total Running Time :	973 Hour 3 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	107	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		45	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.51	kN	No		
HEP :	25.0 %	14.92	kN	Yes 15	Rotations 20	Tablets
HCP :	2.5 %	12.23	kN	Yes 20	Times	
Ref :		11.93	kN			
LCP :	2.5 %	11.63	kN	Yes 20	Times	
LEP :	25.0 %	8.95	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	8.35	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.06	kN	Min :	3.00	kN	Punch NO.;	4
SD :	0.90	%	Max :	3.13	kN	Punch NO.;	28
Mean Main Pressure :	11.73	kN	Min :	9.79	kN	Punch NO.;	52
SD :	7.20	%	Max :	13.25	kN	Punch NO.;	46
Filling Depth :	Increase ; 986	Times	Decrease ;	953	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.14	mm	Current Cam :	Cam B	
Main Air pressure :	0.810	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	52
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	30
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.13	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	3651648	Tablets			
A.W.C Counter :	3635876	Tablets			
HEP :	2963 (0.1%)	Tablets	LEP :	955 (0.0%)	Tablets
GOOD :	3631958 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	ms88737	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	20 Hour 30 Min 12 Sec
Total Counter :	3651648	Total Running Time :	973 Hour 3 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	107	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		45	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.46	kN	No		
HEP :	25.0 %	13.91	kN	Yes 15	Rotations 20	Tablets
HCP :	2.5 %	11.40	kN	Yes 20	Times	
Ref :		11.12	kN			
LCP :	2.5 %	10.85	kN	Yes 20	Times	
LEP :	25.0 %	8.34	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	7.79	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.80	kN	Min :	2.75	kN	Punch NO.;	40
SD :	0.80	%	Max :	2.89	kN	Punch NO.;	48
Mean Main Pressure :	11.18	kN	Min :	9.04	kN	Punch NO.;	52
SD :	11.50	%	Max :	17.10	kN	Punch NO.;	6
Filling Depth :	Increase ;	1051	Times	Decrease ;	1070	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.43	mm
Filling Depth :	6.95	mm	Current Cam :	Cam B	
Main Air pressure :	0.810	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	52
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.17	kN	Max Punch ;	30
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.13	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	3651648	Tablets			
A.W.C Counter :	3635876	Tablets			
HEP :	2963 (0.1%)	Tablets	LEP :	955 (0.0%)	Tablets
GOOD :	3631958 (99.9%)	Tablets			