

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	ms88737	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	00 Hour 59 Min 18 Sec
Total Counter :	4452104	Total Running Time :	977 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	114	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.27	kN	No		
HEP :	25.0 %	14.68	kN	Yes 15	Rotations 20	Tablets
HCP :	2.5 %	12.04	kN	Yes 20	Times	
Ref :		11.74	kN			
LCP :	2.5 %	11.45	kN	Yes 20	Times	
LEP :	25.0 %	8.81	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	8.22	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.03	kN	Min :	2.98	kN	Punch NO.;	42
SD :	0.80	%	Max :	3.09	kN	Punch NO.;	22
Mean Main Pressure :	11.69	kN	Min :	9.98	kN	Punch NO.;	52
SD :	7.60	%	Max :	13.95	kN	Punch NO.;	27
Filling Depth :	Increase ;	1241	Times	Decrease ;	1196	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	32	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.50	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.788	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	114	Min			
Lower Punch Remain Time (S2):	55	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	47
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	4452104	Tablets			
A.W.C Counter :	4436123	Tablets			
HEP :	9704 (0.2%)	Tablets	LEP :	1259 (0.0%)	Tablets
GOOD :	4425160 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	ms88737	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	00 Hour 59 Min 18 Sec
Total Counter :	4452104	Total Running Time :	977 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	114	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.46	kN	No		
HEP :	25.0 %	13.91	kN	Yes 15	Rotations 20	Tablets
HCP :	2.5 %	11.40	kN	Yes 20	Times	
Ref :		11.12	kN			
LCP :	2.5 %	10.85	kN	Yes 20	Times	
LEP :	25.0 %	8.34	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	7.79	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.82	kN	Min :	2.78	kN	Punch NO.;	33
SD :	0.70	%	Max :	2.89	kN	Punch NO.;	28
Mean Main Pressure :	11.15	kN	Min :	9.59	kN	Punch NO.;	20
SD :	9.00	%	Max :	14.02	kN	Punch NO.;	16
Filling Depth :	Increase ;	1474	Times	Decrease ;	1485	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	32	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.43	mm
Filling Depth :	7.19	mm	Current Cam :	Cam B	
Main Air pressure :	0.788	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	114	Min			
Lower Punch Remain Time (S2):	55	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	20
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	47
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	4452104	Tablets			
A.W.C Counter :	4436123	Tablets			
HEP :	9704 (0.2%)	Tablets	LEP :	1259 (0.0%)	Tablets
GOOD :	4425160 (99.8%)	Tablets			