

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500201
Print Interval :	50000 Tablets	Running Time :	01 Hour 18 Min 01 Sec
Total Counter :	180190	Total Running Time :	979 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.15	kN	No		
HEP :	25.0 %	16.49	kN	Yes	15	Rotations
HCP :	2.0 %	13.46	kN	Yes	20	Times
Ref :		13.19	kN			
LCP :	2.0 %	12.93	kN	Yes	20	Times
LEP :	25.0 %	9.89	kN	Yes	15	Rotations
LSP :	30.0 %	9.23	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.06	kN	Min :	4.74	kN	Punch NO.;	59
SD :	2.90	%	Max :	5.44	kN	Punch NO.;	48
Mean Main Pressure :	13.15	kN	Min :	12.12	kN	Punch NO.;	26
SD :	4.50	%	Max :	14.51	kN	Punch NO.;	53
Filling Depth :	Increase ;	104	Times	Decrease ;	87	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.82	mm			
Pre Lower Punch Position ;	3.80	mm	Pre Thickness ;	0.98	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.01	mm	Main Thickness ;	0.52	mm
Filling Depth :	3.59	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	53
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	180190	Tablets			
A.W.C Counter :	172274	Tablets			
HEP :	575 (0.3%)	Tablets	LEP :	100 (0.1%)	Tablets
GOOD :	171599 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500201
Print Interval :	50000 Tablets	Running Time :	01 Hour 18 Min 01 Sec
Total Counter :	180190	Total Running Time :	979 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.94	kN	No		
HEP :	25.0 %	18.21	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	14.86	kN	Yes 20	Times	
Ref :		14.57	kN			
LCP :	2.0 %	14.27	kN	Yes 20	Times	
LEP :	25.0 %	10.92	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	10.20	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.59	kN	Min :	4.33	kN	Punch NO.;	26
SD :	3.10	%	Max :	5.04	kN	Punch NO.;	17
Mean Main Pressure :	14.79	kN	Min :	13.41	kN	Punch NO.;	26
SD :	4.20	%	Max :	16.36	kN	Punch NO.;	17
Filling Depth :	Increase ; 95	Times	Decrease ;	103	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.80	mm	Pre Thickness ;	1.00	mm
Main Upper Punch Position ;	3.50	mm			
Main Lower Punch Position ;	4.01	mm	Main Thickness ;	0.51	mm
Filling Depth :	4.03	mm	Current Cam :	Cam B	
Main Air pressure :	0.800	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	53
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	180190	Tablets			
A.W.C Counter :	172274	Tablets			
HEP :	575 (0.3%)	Tablets	LEP :	100 (0.1%)	Tablets
GOOD :	171599 (99.6%)	Tablets			