

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	pm98770	Batch NO. :	JUM2500201
Print Interval :	50000 Tablets	Running Time :	01 Hour 26 Min 32 Sec
Total Counter :	200048	Total Running Time :	979 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.36	kN	No		
HEP :	25.0 %	16.69	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	13.62	kN	Yes 20	Times	
Ref :		13.35	kN			
LCP :	2.0 %	13.08	kN	Yes 20	Times	
LEP :	25.0 %	10.01	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	9.35	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.07	kN	Min :	4.68	kN	Punch NO.;	31
		3.40	%	Max :	5.52	kN	Punch NO.;	53
Mean Main Pressure :		13.46	kN	Min :	11.91	kN	Punch NO.;	31
	SD :	4.90	%	Max :	14.72	kN	Punch NO.;	53
Filling Depth :	Increase ;	116	Times	Decrease ;	95	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.82	mm			
Pre Lower Punch Position ;	3.80	mm	Pre Thickness ;	0.98	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.01	mm	Main Thickness ;	0.52	mm
Filling Depth :	3.82	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	9
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	42
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	200048	Tablets			
A.W.C Counter :	191928	Tablets			
HEP :	588 (0.3%)	Tablets	LEP :	104 (0.1%)	Tablets
GOOD :	191236 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	pm98770	Batch NO. :	JUM2500201
Print Interval :	50000 Tablets	Running Time :	01 Hour 26 Min 32 Sec
Total Counter :	200048	Total Running Time :	979 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.69	kN	No		
HEP :	25.0 %	18.93	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	15.45	kN	Yes 20	Times	
Ref :		15.14	kN			
LCP :	2.0 %	14.84	kN	Yes 20	Times	
LEP :	25.0 %	11.36	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	10.60	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.70	kN	Min :	4.38	kN	Punch NO.;	59
SD :	3.30	%	Max :	5.09	kN	Punch NO.;	17
Mean Main Pressure :	15.17	kN	Min :	13.85	kN	Punch NO.;	47
SD :	4.30	%	Max :	17.00	kN	Punch NO.;	17
Filling Depth :	Increase ;	100	Times	Decrease ;	114	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.80	mm	Pre Thickness ;	1.00	mm
Main Upper Punch Position ;	3.50	mm			
Main Lower Punch Position ;	4.01	mm	Main Thickness ;	0.51	mm
Filling Depth :	3.77	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	48
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	42
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	200048	Tablets			
A.W.C Counter :	191928	Tablets			
HEP :	588 (0.3%)	Tablets	LEP :	104 (0.1%)	Tablets
GOOD :	191236 (99.6%)	Tablets			