

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	yd98913	Batch NO. :	JUM2500301
Print Interval :	50000 Tablets	Running Time :	01 Hour 17 Min 12 Sec
Total Counter :	180132	Total Running Time :	981 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	13	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.78	kN	No		
HEP :	25.0 %	17.09	kN	Yes	15	Rotations
HCP :	2.0 %	13.95	kN	Yes	20	Times
Ref :		13.67	kN			
LCP :	2.0 %	13.40	kN	Yes	20	Times
LEP :	25.0 %	10.26	kN	Yes	15	Rotations
LSP :	30.0 %	9.57	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.16	kN	Min :	4.78	kN	Punch NO.;	31
SD :	3.90	%	Max :	5.69	kN	Punch NO.;	53
Mean Main Pressure :	13.52	kN	Min :	12.09	kN	Punch NO.;	32
SD :	5.70	%	Max :	15.25	kN	Punch NO.;	53
Filling Depth :	Increase ;	232	Times	Decrease ;	222	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	3	RPM
Pre Upper Punch Position ;	2.82	mm			
Pre Lower Punch Position ;	3.80	mm	Pre Thickness ;	0.98	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.01	mm	Main Thickness ;	0.52	mm
Filling Depth :	3.86	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.802	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	41
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.06	kN	Max Punch ;	15

Tablet Data (N/A)

Total Counter :	180132	Tablets			
A.W.C Counter :	176413	Tablets			
HEP :	0 (0%)	Tablets	LEP :	39 (0.0%)	Tablets
GOOD :	176374 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	yd98913	Batch NO. :	JUM2500301
Print Interval :	50000 Tablets	Running Time :	01 Hour 17 Min 12 Sec
Total Counter :	180132	Total Running Time :	981 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	13	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.69	kN	No		
HEP :	25.0 %	18.93	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	15.45	kN	Yes 20	Times	
Ref :		15.14	kN			
LCP :	2.0 %	14.84	kN	Yes 20	Times	
LEP :	25.0 %	11.36	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	10.60	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.72	kN	Min :	4.37	kN	Punch NO.;	26
SD :	2.80	%	Max :	5.00	kN	Punch NO.;	53
Mean Main Pressure :	15.37	kN	Min :	14.07	kN	Punch NO.;	32
SD :	3.40	%	Max :	16.45	kN	Punch NO.;	53
Filling Depth :	Increase ;	212	Times	Decrease ;	195	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	3	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.80	mm	Pre Thickness ;	1.00	mm
Main Upper Punch Position ;	3.50	mm			
Main Lower Punch Position ;	4.01	mm	Main Thickness ;	0.51	mm
Filling Depth :	3.62	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.802	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	41
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.06	kN	Max Punch ;	15

Tablet Data (N/A)

Total Counter :	180132	Tablets			
A.W.C Counter :	176413	Tablets			
HEP :	0 (0%)	Tablets	LEP :	39 (0.0%)	Tablets
GOOD :	176374 (100.0%)	Tablets			