

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500301
Print Interval :	50000 Tablets	Running Time :	01 Hour 19 Min 27 Sec
Total Counter :	185348	Total Running Time :	981 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	13	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.16	kN	No		
HEP :	25.0 %	17.46	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	14.25	kN	Yes 20	Times	
Ref :		13.97	kN			
LCP :	2.0 %	13.69	kN	Yes 20	Times	
LEP :	25.0 %	10.48	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	9.78	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.17	kN	Min :	4.78	kN	Punch NO.;	32
		3.40	%	Max :	5.51	kN	Punch NO.;	48
Mean Main Pressure :		13.80	kN	Min :	12.15	kN	Punch NO.;	32
	SD :	4.80	%	Max :	15.18	kN	Punch NO.;	64
Filling Depth :	Increase ;	232	Times	Decrease ;	226	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.82	mm			
Pre Lower Punch Position ;	3.80	mm	Pre Thickness ;	0.98	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.01	mm	Main Thickness ;	0.52	mm
Filling Depth :	3.74	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.797	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	12
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	24
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.06	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	185348	Tablets			
A.W.C Counter :	181441	Tablets			
HEP :	0 (0%)	Tablets	LEP :	39 (0.0%)	Tablets
GOOD :	181402 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500301
Print Interval :	50000 Tablets	Running Time :	01 Hour 19 Min 27 Sec
Total Counter :	185348	Total Running Time :	981 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	13	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.69	kN	No		
HEP :	25.0 %	18.93	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	15.45	kN	Yes 20	Times	
Ref :		15.14	kN			
LCP :	2.0 %	14.84	kN	Yes 20	Times	
LEP :	25.0 %	11.36	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	10.60	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.67	kN	Min :	4.36	kN	Punch NO.;	24
SD :	2.90	%	Max :	4.99	kN	Punch NO.;	48
Mean Main Pressure :	15.02	kN	Min :	13.85	kN	Punch NO.;	24
SD :	4.00	%	Max :	16.38	kN	Punch NO.;	43
Filling Depth :	Increase ;	216	Times	Decrease ;	196	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.80	mm	Pre Thickness ;	1.00	mm
Main Upper Punch Position ;	3.50	mm			
Main Lower Punch Position ;	4.01	mm	Main Thickness ;	0.51	mm
Filling Depth :	3.71	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	12
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	49
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.06	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	185348	Tablets			
A.W.C Counter :	181441	Tablets			
HEP :	0 (0%)	Tablets	LEP :	39 (0.0%)	Tablets
GOOD :	181402 (100.0%)	Tablets			