

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG STJU1B00
User ID :	am98755	Batch NO. :	JUM2500205
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 45 Sec
Total Counter :	50026	Total Running Time :	982 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		180000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.20	kN	No		
HEP :	25.0 %	30.00	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	24.48	kN	Yes 20	Times	
Ref :		24.00	kN			
LCP :	2.0 %	23.52	kN	Yes 20	Times	
LEP :	25.0 %	18.00	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	16.80	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.50	kN	Min :	3.42	kN	Punch NO.;	8
SD :	1.20	%	Max :	3.62	kN	Punch NO.;	19
Mean Main Pressure :	24.33	kN	Min :	22.80	kN	Punch NO.;	28
SD :	3.30	%	Max :	26.44	kN	Punch NO.;	13
Filling Depth :	Increase ; 15	Times	Decrease ; 3	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	1.66	mm
Filling Depth :	7.98	mm	Current Cam :	Cam C	
Main Air pressure :	0.779	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.25	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	28
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	50026	Tablets			
A.W.C Counter :	46940	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	46940 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG STJU1B00
User ID :	am98755	Batch NO. :	JUM2500205
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 45 Sec
Total Counter :	50026	Total Running Time :	982 Hour 50 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		180000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.41	kN	No		
HEP :	25.0 %	34.05	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	27.78	kN	Yes 20	Times	
Ref :		27.24	kN			
LCP :	2.0 %	26.69	kN	Yes 20	Times	
LEP :	25.0 %	20.43	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	19.07	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.41	kN	Min :	3.33	kN	Punch NO.;	15
SD :	1.30	%	Max :	3.50	kN	Punch NO.;	35
Mean Main Pressure :	27.30	kN	Min :	25.57	kN	Punch NO.;	28
SD :	3.70	%	Max :	30.39	kN	Punch NO.;	53
Filling Depth :	Increase ; 31	Times	Decrease ; 23	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	1.66	mm
Filling Depth :	7.82	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.779	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.25	kN	Max Punch ;	27
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	28
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	50026	Tablets			
A.W.C Counter :	46940	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	46940 (100.0%)	Tablets			