

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG STJU1B00
User ID :	pm98770	Batch NO. :	JUM2500205
Print Interval :	50000 Tablets	Running Time :	00 Hour 55 Min 53 Sec
Total Counter :	97434	Total Running Time :	983 Hour 14 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		180000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.21	kN	No		
HEP :	25.0 %	30.97	kN	Yes	15	Rotations
HCP :	2.0 %	25.27	kN	Yes	20	Times
Ref :		24.78	kN			
LCP :	2.0 %	24.28	kN	Yes	20	Times
LEP :	25.0 %	18.58	kN	Yes	15	Rotations
LSP :	30.0 %	17.34	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.55	kN	Min :	3.45	kN	Punch NO.;	26
		1.20	%	Max :	3.67	kN	Punch NO.;	40
Mean Main Pressure :		24.62	kN	Min :	22.75	kN	Punch NO.;	44
	SD :	3.30	%	Max :	26.25	kN	Punch NO.;	53
Filling Depth :	Increase ;	50	Times	Decrease ;	24	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.65	mm	Main Thickness ;	1.65	mm
Filling Depth :	8.32	mm	Current Cam :	Cam C	
Main Air pressure :	0.791	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.11	kN	Max Punch ;	33
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	29
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	97434	Tablets			
A.W.C Counter :	91818	Tablets			
HEP :	34 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	91784 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG STJU1B00
User ID :	pm98770	Batch NO. :	JUM2500205
Print Interval :	50000 Tablets	Running Time :	00 Hour 55 Min 53 Sec
Total Counter :	97434	Total Running Time :	983 Hour 14 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		180000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.68	kN	No		
HEP :	25.0 %	34.31	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	28.00	kN	Yes 20	Times	
Ref :		27.45	kN			
LCP :	2.0 %	26.90	kN	Yes 20	Times	
LEP :	25.0 %	20.59	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	19.21	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.47	kN	Min :	3.39	kN	Punch NO.;	37
		1.10	%	Max :	3.55	kN	Punch NO.;	4
Mean Main Pressure :		27.24	kN	Min :	25.15	kN	Punch NO.;	28
	SD :	2.90	%	Max :	28.62	kN	Punch NO.;	1
Filling Depth :	Increase ;	55	Times	Decrease ;	49	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	1.66	mm
Filling Depth :	7.98	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.791	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.11	kN	Max Punch ;	33
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	29
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	97434	Tablets			
A.W.C Counter :	91818	Tablets			
HEP :	34 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	91784 (100.0%)	Tablets			