

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG STJU1B00
User ID :	pm98770	Batch NO. :	JUM2500205
Print Interval :	50000 Tablets	Running Time :	01 Hour 32 Min 06 Sec
Total Counter :	162568	Total Running Time :	983 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		180000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.21	kN	No		
HEP :	25.0 %	30.97	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	25.27	kN	Yes 20	Times	
Ref :		24.78	kN			
LCP :	2.0 %	24.28	kN	Yes 20	Times	
LEP :	25.0 %	18.58	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	17.34	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.52	kN	Min :	3.42	kN	Punch NO.;	1
SD :	1.00	%	Max :	3.60	kN	Punch NO.;	30
Mean Main Pressure :	24.17	kN	Min :	22.90	kN	Punch NO.;	2
SD :	2.10	%	Max :	25.15	kN	Punch NO.;	17
Filling Depth :	Increase ;	109	Times	Decrease ;	26	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.65	mm	Main Thickness ;	1.65	mm
Filling Depth :	9.77	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.805	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.27	kN	Max Punch ;	26
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	13
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	162568	Tablets			
A.W.C Counter :	156752	Tablets			
HEP :	117 (0.1%)	Tablets	LEP :	169 (0.1%)	Tablets
GOOD :	156466 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG STJU1B00
User ID :	pm98770	Batch NO. :	JUM2500205
Print Interval :	50000 Tablets	Running Time :	01 Hour 32 Min 06 Sec
Total Counter :	162568	Total Running Time :	983 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		180000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.68	kN	No		
HEP :	25.0 %	34.31	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	28.00	kN	Yes 20	Times	
Ref :		27.45	kN			
LCP :	2.0 %	26.90	kN	Yes 20	Times	
LEP :	25.0 %	20.59	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	19.21	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.06	kN	Min :	2.95	kN	Punch NO.;	45
SD :	2.50	%	Max :	3.37	kN	Punch NO.;	1
Mean Main Pressure :	19.23	kN	Min :	16.69	kN	Punch NO.;	52
SD :	5.70	%	Max :	22.27	kN	Punch NO.;	14
Filling Depth :	Increase ;	133	Times	Decrease ;	64	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	1.66	mm
Filling Depth :	9.83	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.805	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.25	kN	Max Punch ;	53
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	13
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	162568	Tablets			
A.W.C Counter :	156752	Tablets			
HEP :	117 (0.1%)	Tablets	LEP :	169 (0.1%)	Tablets
GOOD :	156466 (99.8%)	Tablets			