

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG STJU1B00
User ID :	rp98927	Batch NO. :	JUM2500305
Print Interval :	50000 Tablets	Running Time :	01 Hour 18 Min 04 Sec
Total Counter :	135566	Total Running Time :	985 Hour 9 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		180000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.21	kN	No		
HEP :	25.0 %	30.97	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	25.27	kN	Yes 20	Times	
Ref :		24.78	kN			
LCP :	2.0 %	24.28	kN	Yes 20	Times	
LEP :	25.0 %	18.58	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	17.34	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.58	kN	Min :	3.49	kN	Punch NO.;	50
SD :	1.40	%	Max :	3.72	kN	Punch NO.;	36
Mean Main Pressure :	25.10	kN	Min :	23.60	kN	Punch NO.;	44
SD :	2.50	%	Max :	26.41	kN	Punch NO.;	13
Filling Depth :	Increase ;	182	Times	Decrease ;	60	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.65	mm	Main Thickness ;	1.66	mm
Filling Depth :	8.90	mm	Current Cam :	Cam C	
Main Air pressure :	0.775	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.10	kN	Max Punch ;	29
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	13
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	29

Tablet Data (N/A)

Total Counter :	135566	Tablets			
A.W.C Counter :	131988	Tablets			
HEP :	0 (0%)	Tablets	LEP :	12 (0.0%)	Tablets
GOOD :	131976 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG STJU1B00
User ID :	rp98927	Batch NO. :	JUM2500305
Print Interval :	50000 Tablets	Running Time :	01 Hour 18 Min 04 Sec
Total Counter :	135566	Total Running Time :	985 Hour 9 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		180000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.68	kN	No		
HEP :	25.0 %	34.31	kN	Yes	15	Rotations
HCP :	2.0 %	28.00	kN	Yes	20	Times
Ref :		27.45	kN			
LCP :	2.0 %	26.90	kN	Yes	20	Times
LEP :	25.0 %	20.59	kN	Yes	15	Rotations
LSP :	30.0 %	19.21	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.48	kN	Min :	3.38	kN	Punch NO.;	8
SD :	1.70	%	Max :	3.61	kN	Punch NO.;	36
Mean Main Pressure :	27.52	kN	Min :	25.38	kN	Punch NO.;	34
SD :	3.60	%	Max :	29.67	kN	Punch NO.;	13
Filling Depth :	Increase ;	221	Times	Decrease ;	123	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	1.67	mm
Filling Depth :	8.96	mm	Current Cam :	Cam C	
Main Air pressure :	0.775	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.10	kN	Max Punch ;	29
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	24
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	29

Tablet Data (N/A)

Total Counter :	135566	Tablets			
A.W.C Counter :	131988	Tablets			
HEP :	0 (0%)	Tablets	LEP :	12 (0.0%)	Tablets
GOOD :	131976 (100.0%)	Tablets			