

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	ka98463	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	05 Hour 54 Min 38 Sec
Total Counter :	900454	Total Running Time :	991 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.30	kN	No		
HEP :	25.0 %	20.48	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	16.71	kN	Yes 20	Times	
Ref :		16.38	kN			
LCP :	2.0 %	16.06	kN	Yes 20	Times	
LEP :	25.0 %	12.29	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	11.47	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.14	kN	Min :	4.91	kN	Punch NO.;	18
SD :	2.00	%	Max :	5.35	kN	Punch NO.;	50
Mean Main Pressure :	16.52	kN	Min :	14.92	kN	Punch NO.;	30
SD :	4.20	%	Max :	18.49	kN	Punch NO.;	14
Filling Depth :	Increase ; 303	Times	Decrease ;	335	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.46	mm
Filling Depth :	6.96	mm	Current Cam :	Cam C	
Main Air pressure :	0.777	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.21	kN	Max Punch ;	42
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.39	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.19	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	900454	Tablets			
A.W.C Counter :	888533	Tablets			
HEP :	651 (0.1%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	887881 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	ka98463	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	05 Hour 54 Min 38 Sec
Total Counter :	900454	Total Running Time :	991 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	22.25	kN	No		
HEP :	25.0 %	21.40	kN	Yes	15	Rotations
HCP :	2.0 %	17.46	kN	Yes	20	Times
Ref :		17.12	kN			
LCP :	2.0 %	16.77	kN	Yes	20	Times
LEP :	25.0 %	12.84	kN	Yes	15	Rotations
LSP :	30.0 %	11.98	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	5.46	kN	Min :	5.17	kN	Punch NO.;	26
SD :	2.70	%	Max :	5.73	kN	Punch NO.;	8
Mean Main Pressure :	17.10	kN	Min :	15.78	kN	Punch NO.;	31
SD :	5.20	%	Max :	19.12	kN	Punch NO.;	53
Filling Depth :	Increase ;	293	Times	Decrease ;	287	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.61	mm
Filling Depth :	7.00	mm	Current Cam :	Cam C	
Main Air pressure :	0.777	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.23	kN	Max Punch ;	42
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.39	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.19	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	900454	Tablets			
A.W.C Counter :	888533	Tablets			
HEP :	651 (0.1%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	887881 (99.9%)	Tablets			