

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	rp98927	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	07 Hour 14 Min 05 Sec
Total Counter :	1100548	Total Running Time :	992 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.95	kN	No		
HEP :	25.0 %	20.15	kN	Yes	15	Rotations
HCP :	2.0 %	16.44	kN	Yes	20	Times
Ref :		16.12	kN			
LCP :	2.0 %	15.79	kN	Yes	20	Times
LEP :	25.0 %	12.09	kN	Yes	15	Rotations
LSP :	30.0 %	11.28	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.11	kN	Min :	4.82	kN	Punch NO.;	25
SD :	2.50	%	Max :	5.35	kN	Punch NO.;	36
Mean Main Pressure :	16.49	kN	Min :	14.96	kN	Punch NO.;	4
SD :	4.70	%	Max :	18.18	kN	Punch NO.;	50
Filling Depth :	Increase ;	337	Times	Decrease ;	360	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.46	mm
Filling Depth :	7.11	mm	Current Cam :	Cam C	
Main Air pressure :	0.783	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	32
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.44	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1100548	Tablets			
A.W.C Counter :	1085797	Tablets			
HEP :	654 (0.1%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	1085142 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	rp98927	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	07 Hour 14 Min 05 Sec
Total Counter :	1100548	Total Running Time :	992 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.73	kN	No		
HEP :	25.0 %	20.89	kN	Yes	15	Rotations
HCP :	2.0 %	17.05	kN	Yes	20	Times
Ref :		16.71	kN			
LCP :	2.0 %	16.38	kN	Yes	20	Times
LEP :	25.0 %	12.53	kN	Yes	15	Rotations
LSP :	30.0 %	11.70	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	5.17	kN	Min :	4.91	kN	Punch NO.;	24
SD :	2.90	%	Max :	5.64	kN	Punch NO.;	35
Mean Main Pressure :	16.85	kN	Min :	15.42	kN	Punch NO.;	36
SD :	3.90	%	Max :	18.48	kN	Punch NO.;	53
Filling Depth :	Increase ;	313	Times	Decrease ;	302	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.61	mm
Filling Depth :	7.01	mm	Current Cam :	Cam C	
Main Air pressure :	0.783	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.16	kN	Max Punch ;	32
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.44	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1100548	Tablets			
A.W.C Counter :	1085850	Tablets			
HEP :	654 (0.1%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	1085195 (99.9%)	Tablets			