

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	rp98927	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	07 Hour 37 Min 45 Sec
Total Counter :	1150568	Total Running Time :	993 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.95	kN	No		
HEP :	25.0 %	20.15	kN	Yes	15	Rotations
HCP :	2.0 %	16.44	kN	Yes	20	Times
Ref :		16.12	kN			
LCP :	2.0 %	15.79	kN	Yes	20	Times
LEP :	25.0 %	12.09	kN	Yes	15	Rotations
LSP :	30.0 %	11.28	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.12	kN	Min :	4.87	kN	Punch NO.;	27
SD :	2.80	%	Max :	5.46	kN	Punch NO.;	50
Mean Main Pressure :	16.44	kN	Min :	14.71	kN	Punch NO.;	43
SD :	5.00	%	Max :	18.42	kN	Punch NO.;	10
Filling Depth :	Increase ;	345	Times	Decrease ;	365	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.46	mm
Filling Depth :	7.20	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	33
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.55	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1150568	Tablets			
A.W.C Counter :	1135829	Tablets			
HEP :	654 (0.1%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	1135174 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	rp98927	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	07 Hour 37 Min 45 Sec
Total Counter :	1150568	Total Running Time :	993 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.73	kN	No		
HEP :	25.0 %	20.89	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	17.05	kN	Yes 20	Times	
Ref :		16.71	kN			
LCP :	2.0 %	16.38	kN	Yes 20	Times	
LEP :	25.0 %	12.53	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	11.70	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	5.08	kN	Min :	4.74	kN	Punch NO.;	21
SD :	3.10	%	Max :	5.41	kN	Punch NO.;	47
Mean Main Pressure :	16.56	kN	Min :	15.38	kN	Punch NO.;	30
SD :	4.40	%	Max :	18.24	kN	Punch NO.;	50
Filling Depth :	Increase ;	318	Times	Decrease ;	303	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.61	mm
Filling Depth :	7.13	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	33
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.58	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1150568	Tablets			
A.W.C Counter :	1135829	Tablets			
HEP :	654 (0.1%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	1135174 (99.9%)	Tablets			