

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	yd98913	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	11 Hour 58 Min 02 Sec
Total Counter :	1700744	Total Running Time :	997 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.42	kN	No		
HEP :	25.0 %	20.59	kN	Yes	15	Rotations
HCP :	2.0 %	16.81	kN	Yes	20	Times
Ref :		16.48	kN			
LCP :	2.0 %	16.15	kN	Yes	20	Times
LEP :	25.0 %	12.36	kN	Yes	15	Rotations
LSP :	30.0 %	11.53	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.14	kN	Min :	4.84	kN	Punch NO.;	14
SD :	3.90	%	Max :	5.74	kN	Punch NO.;	52
Mean Main Pressure :	16.41	kN	Min :	14.39	kN	Punch NO.;	30
SD :	6.20	%	Max :	19.08	kN	Punch NO.;	12
Filling Depth :	Increase ;	592	Times	Decrease ;	519	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.46	mm
Filling Depth :	7.66	mm	Current Cam :	Cam C	
Main Air pressure :	0.759	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	33
Lower Punch :	Average ;	0.18	kN		
	Max ;	1.09	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.20	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1700744	Tablets			
A.W.C Counter :	1682690	Tablets			
HEP :	1373 (0.1%)	Tablets	LEP :	126 (0.0%)	Tablets
GOOD :	1681191 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	yd98913	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	11 Hour 58 Min 02 Sec
Total Counter :	1700744	Total Running Time :	997 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.55	kN	No		
HEP :	25.0 %	20.72	kN	Yes	15	Rotations
HCP :	2.0 %	16.91	kN	Yes	20	Times
Ref :		16.58	kN			
LCP :	2.0 %	16.25	kN	Yes	20	Times
LEP :	25.0 %	12.43	kN	Yes	15	Rotations
LSP :	30.0 %	11.60	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	5.11	kN	Min :	4.79	kN	Punch NO.;	33
SD :	4.20	%	Max :	5.87	kN	Punch NO.;	39
Mean Main Pressure :	16.82	kN	Min :	14.57	kN	Punch NO.;	31
SD :	5.70	%	Max :	19.04	kN	Punch NO.;	1
Filling Depth :	Increase ;	471	Times	Decrease ;	383	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.61	mm
Filling Depth :	7.70	mm	Current Cam :	Cam C	
Main Air pressure :	0.759	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	1
Lower Punch :	Average ;	0.18	kN		
	Max ;	1.09	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.20	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1700744	Tablets			
A.W.C Counter :	1682690	Tablets			
HEP :	1373 (0.1%)	Tablets	LEP :	126 (0.0%)	Tablets
GOOD :	1681191 (99.9%)	Tablets			