

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	yd98913	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	12 Hour 21 Min 41 Sec
Total Counter :	1750760	Total Running Time :	997 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.42	kN	No		
HEP :	25.0 %	20.59	kN	Yes	15	Rotations 20 Tablets
HCP :	2.0 %	16.81	kN	Yes	20	Times
Ref :		16.48	kN			
LCP :	2.0 %	16.15	kN	Yes	20	Times
LEP :	25.0 %	12.36	kN	Yes	15	Rotations 20 Tablets
LSP :	30.0 %	11.53	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.11	kN	Min :	4.72	kN	Punch NO.;	27
SD :	3.70	%	Max :	5.58	kN	Punch NO.;	36
Mean Main Pressure :	16.69	kN	Min :	15.20	kN	Punch NO.;	43
SD :	5.20	%	Max :	19.06	kN	Punch NO.;	50
Filling Depth :	Increase ;	615	Times	Decrease ;	544	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.46	mm
Filling Depth :	7.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.766	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.13	kN	Max Punch ;	27
Lower Punch :	Average ;	0.18	kN		
	Max ;	1.12	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.22	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1750760	Tablets			
A.W.C Counter :	1732722	Tablets			
HEP :	1377 (0.1%)	Tablets	LEP :	126 (0.0%)	Tablets
GOOD :	1731219 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	yd98913	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	12 Hour 21 Min 41 Sec
Total Counter :	1750760	Total Running Time :	997 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.55	kN	No		
HEP :	25.0 %	20.72	kN	Yes	15	Rotations
HCP :	2.0 %	16.91	kN	Yes	20	Times
Ref :		16.58	kN			
LCP :	2.0 %	16.25	kN	Yes	20	Times
LEP :	25.0 %	12.43	kN	Yes	15	Rotations
LSP :	30.0 %	11.60	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	5.05	kN	Min :	4.71	kN	Punch NO.;	12
SD :	3.70	%	Max :	5.61	kN	Punch NO.;	39
Mean Main Pressure :	16.35	kN	Min :	14.86	kN	Punch NO.;	25
SD :	5.60	%	Max :	19.08	kN	Punch NO.;	10
Filling Depth :	Increase ;	489	Times	Decrease ;	400	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.61	mm
Filling Depth :	7.73	mm	Current Cam :	Cam C	
Main Air pressure :	0.766	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.14	kN	Max Punch ;	1
Lower Punch :	Average ;	0.18	kN		
	Max ;	1.12	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.22	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1750760	Tablets			
A.W.C Counter :	1732722	Tablets			
HEP :	1377 (0.1%)	Tablets	LEP :	126 (0.0%)	Tablets
GOOD :	1731219 (99.9%)	Tablets			