

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pm98770	Batch NO. :	IUM2501260
Print Interval :	50000 Tablets	Running Time :	01 Hour 01 Min 24 Sec
Total Counter :	105598	Total Running Time :	1000 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	335	%	Manual ;	19	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.01	kN	No		
HEP :	25.0 %	23.09	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	18.84	kN	Yes 20	Times	
Ref :		18.47	kN			
LCP :	2.0 %	18.10	kN	Yes 20	Times	
LEP :	25.0 %	13.85	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	12.93	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	7.70	kN	Min :	6.96	kN	Punch NO.;	30
SD :	4.50	%	Max :	8.34	kN	Punch NO.;	49
Mean Main Pressure :	18.29	kN	Min :	16.54	kN	Punch NO.;	44
SD :	5.10	%	Max :	20.13	kN	Punch NO.;	25
Filling Depth :	Increase ; 2	Times	Decrease ;	25	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	60	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	3.35	mm
Filling Depth :	10.87	mm	Current Cam :	Cam C	
Main Air pressure :	0.787	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.29	kN	Max Punch ;	52
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	41
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	15

Tablet Data (N/A)

Total Counter :	105598	Tablets			
A.W.C Counter :	97453	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	97453 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pm98770	Batch NO. :	IUM2501260
Print Interval :	50000 Tablets	Running Time :	01 Hour 01 Min 24 Sec
Total Counter :	105598	Total Running Time :	1000 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	277	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.00	kN	No		
HEP :	25.0 %	25.96	kN	Yes	15	Rotations
HCP :	2.0 %	21.18	kN	Yes	20	Times
Ref :		20.77	kN			
LCP :	2.0 %	20.35	kN	Yes	20	Times
LEP :	25.0 %	15.58	kN	Yes	15	Rotations
LSP :	30.0 %	14.54	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.19	kN	Min :	7.50	kN	Punch NO.;	31
SD :	3.70	%	Max :	8.85	kN	Punch NO.;	45
Mean Main Pressure :	20.85	kN	Min :	19.07	kN	Punch NO.;	44
SD :	4.30	%	Max :	22.74	kN	Punch NO.;	51
Filling Depth :	Increase ;	9	Times	Decrease ;	5	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	3.45	mm
Filling Depth :	10.72	mm	Current Cam :	Cam C	
Main Air pressure :	0.787	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.27	kN	Max Punch ;	1
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	41
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	15

Tablet Data (N/A)

Total Counter :	105598	Tablets			
A.W.C Counter :	97453	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	97453 (100.0%)	Tablets			