

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pb97604	Batch NO. :	IUM2501260
Print Interval :	50000 Tablets	Running Time :	08 Hour 10 Min 51 Sec
Total Counter :	905868	Total Running Time :	1008 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	490	%	Manual ;	19	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.55	kN	No		
HEP :	25.0 %	24.56	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	20.04	kN	Yes 20	Times	
Ref :		19.65	kN			
LCP :	2.0 %	19.26	kN	Yes 20	Times	
LEP :	25.0 %	14.74	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.76	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.07	kN	Min :	7.32	kN	Punch NO.;	31
SD :	3.80	%	Max :	8.63	kN	Punch NO.;	42
Mean Main Pressure :	19.87	kN	Min :	18.61	kN	Punch NO.;	44
SD :	3.90	%	Max :	22.09	kN	Punch NO.;	52
Filling Depth :	Increase ;	290	Times	Decrease ;	301	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	83	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	3.35	mm
Filling Depth :	10.51	mm	Current Cam :	Cam C	
Main Air pressure :	0.797	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.24	kN	Max Punch ;	1
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.26	kN	Max Punch ;	17
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.15	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	905868	Tablets			
A.W.C Counter :	895888	Tablets			
HEP :	97 (0.0%)	Tablets	LEP :	317 (0.0%)	Tablets
GOOD :	895474 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pb97604	Batch NO. :	IUM2501260
Print Interval :	50000 Tablets	Running Time :	08 Hour 10 Min 51 Sec
Total Counter :	905868	Total Running Time :	1008 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	410	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.88	kN	No		
HEP :	25.0 %	25.85	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.09	kN	Yes 20	Times	
Ref :		20.68	kN			
LCP :	2.0 %	20.27	kN	Yes 20	Times	
LEP :	25.0 %	15.51	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	14.48	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.08	kN	Min :	7.33	kN	Punch NO.;	48
SD :	4.90	%	Max :	8.98	kN	Punch NO.;	4
Mean Main Pressure :	20.95	kN	Min :	18.94	kN	Punch NO.;	44
SD :	5.90	%	Max :	25.13	kN	Punch NO.;	51
Filling Depth :	Increase ;	113	Times	Decrease ;	113	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	70	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	3.45	mm
Filling Depth :	10.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.797	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.24	kN	Max Punch ;	52
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.26	kN	Max Punch ;	17
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.15	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	905868	Tablets			
A.W.C Counter :	895888	Tablets			
HEP :	97 (0.0%)	Tablets	LEP :	317 (0.0%)	Tablets
GOOD :	895474 (100.0%)	Tablets			