

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pb97604	Batch NO. :	SHM2501210
Print Interval :	50000 Tablets	Running Time :	19 Hour 10 Min 08 Sec
Total Counter :	1801410	Total Running Time :	1031 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.39	kN	No		
HEP :	25.0 %	22.49	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	18.35	kN	Yes 10	Times	
Ref :		17.99	kN			
LCP :	2.0 %	17.63	kN	Yes 10	Times	
LEP :	25.0 %	13.49	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	12.59	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.43	kN	Min :	4.32	kN	Punch NO.;	27
SD :	1.00	%	Max :	4.54	kN	Punch NO.;	1
Mean Main Pressure :	18.01	kN	Min :	16.99	kN	Punch NO.;	77
SD :	2.50	%	Max :	19.06	kN	Punch NO.;	76
Filling Depth :	Increase ; 47	Times	Decrease ;	105	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.95	mm
Filling Depth :	8.36	mm	Current Cam :	Cam C	
Main Air pressure :	0.769	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.30	kN	Max Punch ;	6
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	1801410	Tablets			
A.W.C Counter :	1796557	Tablets			
HEP :	13 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1796544 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pb97604	Batch NO. :	SHM2501210
Print Interval :	50000 Tablets	Running Time :	19 Hour 10 Min 08 Sec
Total Counter :	1801410	Total Running Time :	1031 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	22.91	kN	No		
HEP :	25.0 %	22.03	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	17.97	kN	Yes 10	Times	
Ref :		17.62	kN			
LCP :	2.0 %	17.27	kN	Yes 10	Times	
LEP :	25.0 %	13.22	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	12.34	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.27	kN	Min :	4.16	kN	Punch NO.;	27
SD :	1.30	%	Max :	4.45	kN	Punch NO.;	35
Mean Main Pressure :	17.83	kN	Min :	16.51	kN	Punch NO.;	27
SD :	3.80	%	Max :	20.23	kN	Punch NO.;	76
Filling Depth :	Increase ; 170	Times	Decrease ;	176	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	2.05	mm
Filling Depth :	7.79	mm	Current Cam :	Cam C	
Main Air pressure :	0.769	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.30	kN	Max Punch ;	6
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	1801410	Tablets			
A.W.C Counter :	1796557	Tablets			
HEP :	13 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1796544 (100.0%)	Tablets			