

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pm98770	Batch NO. :	SHM2501210
Print Interval :	50000 Tablets	Running Time :	21 Hour 29 Min 06 Sec
Total Counter :	2401812	Total Running Time :	1033 Hour 34 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.71	kN	No		
HEP :	25.0 %	20.87	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	17.03	kN	Yes 10	Times	
Ref :		16.70	kN			
LCP :	2.0 %	16.36	kN	Yes 10	Times	
LEP :	25.0 %	12.52	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.44	kN	Min :	4.33	kN	Punch NO.;	25
SD :	1.20	%	Max :	4.63	kN	Punch NO.;	35
Mean Main Pressure :	16.70	kN	Min :	15.82	kN	Punch NO.;	32
SD :	2.80	%	Max :	17.97	kN	Punch NO.;	35
Filling Depth :	Increase ; 68	Times	Decrease ;	133	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.03	mm
Filling Depth :	8.16	mm	Current Cam :	Cam C	
Main Air pressure :	0.768	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.30	kN	Max Punch ;	57
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	29

Tablet Data (N/A)

Total Counter :	2401812	Tablets			
A.W.C Counter :	2396586	Tablets			
HEP :	26 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2396560 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pm98770	Batch NO. :	SHM2501210
Print Interval :	50000 Tablets	Running Time :	21 Hour 29 Min 06 Sec
Total Counter :	2401812	Total Running Time :	1033 Hour 34 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	22.00	kN	No		
HEP :	25.0 %	21.15	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	17.26	kN	Yes 10	Times	
Ref :		16.92	kN			
LCP :	2.0 %	16.58	kN	Yes 10	Times	
LEP :	25.0 %	12.69	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.85	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.43	kN	Min :	4.32	kN	Punch NO.;	29
SD :	1.20	%	Max :	4.57	kN	Punch NO.;	35
Mean Main Pressure :	17.06	kN	Min :	15.95	kN	Punch NO.;	14
SD :	3.50	%	Max :	18.65	kN	Punch NO.;	35
Filling Depth :	Increase ;	215	Times	Decrease ;	218	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.64	mm	Main Thickness ;	2.14	mm
Filling Depth :	8.17	mm	Current Cam :	Cam C	
Main Air pressure :	0.768	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.30	kN	Max Punch ;	57
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	29

Tablet Data (N/A)

Total Counter :	2401812	Tablets			
A.W.C Counter :	2396586	Tablets			
HEP :	26 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2396560 (100.0%)	Tablets			