

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	rp98927	Batch NO. :	SHM2501310
Print Interval :	50000 Tablets	Running Time :	01 Hour 21 Min 11 Sec
Total Counter :	350302	Total Running Time :	1037 Hour 10 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.15	kN	No		
HEP :	25.0 %	20.33	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.59	kN	Yes 10	Times	
Ref :		16.27	kN			
LCP :	2.0 %	15.94	kN	Yes 10	Times	
LEP :	25.0 %	12.20	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.39	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.59	kN	Min :	4.50	kN	Punch NO.;	33
SD :	1.00	%	Max :	4.71	kN	Punch NO.;	51
Mean Main Pressure :	16.22	kN	Min :	15.41	kN	Punch NO.;	24
SD :	2.20	%	Max :	17.30	kN	Punch NO.;	3
Filling Depth :	Increase ; 124	Times	Decrease ;	175	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.03	mm
Filling Depth :	7.86	mm	Current Cam :	Cam C	
Main Air pressure :	0.750	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.35	kN	Max Punch ;	18
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	74
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	77

Tablet Data (N/A)

Total Counter :	350302	Tablets			
A.W.C Counter :	347185	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	347162 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	rp98927	Batch NO. :	SHM2501310
Print Interval :	50000 Tablets	Running Time :	01 Hour 21 Min 11 Sec
Total Counter :	350302	Total Running Time :	1037 Hour 10 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.66	kN	No		
HEP :	25.0 %	19.87	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.21	kN	Yes 10	Times	
Ref :		15.89	kN			
LCP :	2.0 %	15.57	kN	Yes 10	Times	
LEP :	25.0 %	11.92	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.12	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.64	kN	Min :	4.53	kN	Punch NO.;	71
SD :	1.20	%	Max :	4.78	kN	Punch NO.;	3
Mean Main Pressure :	16.16	kN	Min :	15.21	kN	Punch NO.;	32
SD :	3.10	%	Max :	17.54	kN	Punch NO.;	3
Filling Depth :	Increase ;	405	Times	Decrease ;	396	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.64	mm	Main Thickness ;	2.14	mm
Filling Depth :	7.61	mm	Current Cam :	Cam C	
Main Air pressure :	0.750	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.35	kN	Max Punch ;	18
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	74
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	77

Tablet Data (N/A)

Total Counter :	350302	Tablets			
A.W.C Counter :	347262	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	347239 (100.0%)	Tablets			