

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	rp98927	Batch NO. :	SHM2501310
Print Interval :	50000 Tablets	Running Time :	02 Hour 30 Min 40 Sec
Total Counter :	650522	Total Running Time :	1038 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.15	kN	No		
HEP :	25.0 %	20.33	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.59	kN	Yes 10	Times	
Ref :		16.27	kN			
LCP :	2.0 %	15.94	kN	Yes 10	Times	
LEP :	25.0 %	12.20	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.39	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.58	kN	Min :	4.44	kN	Punch NO.;	8
SD :	1.00	%	Max :	4.67	kN	Punch NO.;	58
Mean Main Pressure :	16.45	kN	Min :	15.47	kN	Punch NO.;	37
SD :	2.50	%	Max :	17.17	kN	Punch NO.;	75
Filling Depth :	Increase ;	138	Times	Decrease ;	191	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.03	mm
Filling Depth :	7.80	mm	Current Cam :	Cam C	
Main Air pressure :	0.805	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.32	kN	Max Punch ;	19
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	65

Tablet Data (N/A)

Total Counter :	650522	Tablets			
A.W.C Counter :	647408	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	647384 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	rp98927	Batch NO. :	SHM2501310
Print Interval :	50000 Tablets	Running Time :	02 Hour 30 Min 40 Sec
Total Counter :	650522	Total Running Time :	1038 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.47	kN	No		
HEP :	25.0 %	20.64	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.84	kN	Yes 10	Times	
Ref :		16.51	kN			
LCP :	2.0 %	16.18	kN	Yes 10	Times	
LEP :	25.0 %	12.38	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.56	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.68	kN	Min :	4.55	kN	Punch NO.;	22
SD :	1.30	%	Max :	4.86	kN	Punch NO.;	3
Mean Main Pressure :	16.72	kN	Min :	15.48	kN	Punch NO.;	12
SD :	3.40	%	Max :	18.27	kN	Punch NO.;	3
Filling Depth :	Increase ;	496	Times	Decrease ;	488	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.64	mm	Main Thickness ;	2.14	mm
Filling Depth :	7.74	mm	Current Cam :	Cam C	
Main Air pressure :	0.805	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.32	kN	Max Punch ;	19
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	75

Tablet Data (N/A)

Total Counter :	650522	Tablets			
A.W.C Counter :	647408	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	647384 (100.0%)	Tablets			