

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pn98247	Batch NO. :	SHM2501310
Print Interval :	50000 Tablets	Running Time :	05 Hour 01 Min 13 Sec
Total Counter :	1301014	Total Running Time :	1040 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.15	kN	No		
HEP :	25.0 %	20.33	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.59	kN	Yes 10	Times	
Ref :		16.27	kN			
LCP :	2.0 %	15.94	kN	Yes 10	Times	
LEP :	25.0 %	12.20	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.39	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.46	kN	Min :	4.34	kN	Punch NO.;	36
SD :	1.10	%	Max :	4.61	kN	Punch NO.;	75
Mean Main Pressure :	15.84	kN	Min :	14.78	kN	Punch NO.;	34
SD :	2.70	%	Max :	16.97	kN	Punch NO.;	75
Filling Depth :	Increase ;	178	Times	Decrease ;	230	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.03	mm
Filling Depth :	7.80	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.744	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	39	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.25	kN	Max Punch ;	13
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	1301014	Tablets			
A.W.C Counter :	1297639	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	1297614 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pn98247	Batch NO. :	SHM2501310
Print Interval :	50000 Tablets	Running Time :	05 Hour 01 Min 13 Sec
Total Counter :	1301014	Total Running Time :	1040 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.47	kN	No		
HEP :	25.0 %	20.64	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.84	kN	Yes 10	Times	
Ref :		16.51	kN			
LCP :	2.0 %	16.18	kN	Yes 10	Times	
LEP :	25.0 %	12.38	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.56	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.54	kN	Min :	4.43	kN	Punch NO.;	13
SD :	1.30	%	Max :	4.80	kN	Punch NO.;	76
Mean Main Pressure :	16.43	kN	Min :	15.32	kN	Punch NO.;	11
SD :	3.80	%	Max :	18.97	kN	Punch NO.;	76
Filling Depth :	Increase ;	713	Times	Decrease ;	706	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.64	mm	Main Thickness ;	2.14	mm
Filling Depth :	7.71	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.744	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	39	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.25	kN	Max Punch ;	13
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.11	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	1301014	Tablets			
A.W.C Counter :	1297639	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	1297614 (100.0%)	Tablets			